BAF Series

13/32″ x 1-1/2″ 250Vac Fast-acting supplemental fuses



250Vac
1/4 to 30A

Description

Fast-acting, supplemental fuse.

For superior protection, Bussmann recommends upgrading to Low-Peak™ Class CC fuses. See data sheet # 1023.

Catalog symbol – color code

- BAF - Green (250Vac max 1/4 to 30A)

Ratings

	Interrupting Rating at System Voltage		Agency Information	
Fuse Amp Range	250 Vac	125 Vac	UL	CSA
1/4 to 1	35A	10kA	-	X
1-1/2 to 2-1/2	100A	10kA	-	X
3	100A	10kA	X	X
4 to 10	200A	10kA	X	X
12 to 15	750A	10kA	X	X
20 to 30	200A	10kA	-	-

Agency information

- CE
- UL Listed, Std. 248-14, 250Vac (3 to 15A) Guide JDYX, File E19180
- CSA Certified, 250Vac (1/4 to 15A) Class 1422-01, File 53787

Catalog numbers (amps)

BAF-1/4	BAF-1-8/10	BAF-6	BAF-12
BAF-1/2	BAF-2	BAF-6-1/4	BAF-15
BAF-6/10	BAF-2-1/2	BAF-7	BAF-20
BAF-8/10	BAF-3	BAF-8	BAF-25
BAF-1	BAF-4	BAF-9	BAF-30
BAF-1-1/2	BAF-5	BAF-10	

Carton quantity

Amps	Qty
1/4 to 30	10

Dimensions - in (mm)



Features

- Color coded green for 250Vac maximum voltage rating
- Fiber tube construction
- Nickel-plated brass endcaps.

Typical applications

- General purpose circuits
- Lighting circuit protection
- Meter circuits

Recommended fuse blocks/fuse holders

Series	Description	Data Sheet #
Blocks		
BMM Series	1-, 2- & 3-Pole modular blocks with optional covers	10235
BM Series	1-, 2- & 3-Pole blocks	1104
DIN-Rail Holders / Switches		
CCP-_-30M	1-, 2- & 3-Pole switch	1157
CHM Series	1-, 2- & 3-Pole	3185
Optima NG	3-Pole protection module	1109
Optima	3-Pole holder	1102
Optima	3-Pole holder + switch	1103
Panel Mount Holders		
HPM & HPM-D	1-Pole holder	2112
HPC-D	1-Pole holder	2109
HPS2	2-Pole holder	2140
HPF, HPF-C & HPF-WT	1-Pole holder	2114
HPS	1-Pole holder	2113
HPG & HPD	1-Pole holder	2108
In-line Holders		
HEB	1-Pole holder	2127
HEX	2-Pole holder	2126
Fuseclips		
1A3400, 5956 & 5960 Series	PCB Fuseclips	2132
Fuse Covers		
SAMI-7	Finger-safe fuse cover	1204

Bussmann
by EATON

Time-current characteristic curves – total clear



The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Eaton's Bussmann Business
114 Old State Road
Ellisville, MO 63021
United States
www.Bussmann.com

Powering Business Worldwide

© 2014 Eaton
All Rights Reserved
Publication No. 2011 - BU-SB14288
April 2014

Eaton is a registered trademark.

All other trademarks are property of their respective owners.