TEGERA®





TEGERA® INFINITY 8802

Learn more

GREAT FIT, DOUBLE COATED PALM DIPPED

Precision work glove with a unique feeling and ultimate dexterity for jobs in greasy and oily environments. Ultra light thanks to 18 gg knitting. Nitrile double dipped with microfoam coated palm for better grip performance. Withstands contact heat up to 100°C/212°F. Anatomically designed, passes Derma-tests and has Oeko-Tex certificate.

CHARACTERISTICS

- Durable
- Extremely good fingertip sensitivity
- Extra flexible
- Extra comfortable
- Good grip

FUNCTIONS

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs
- Thin
- Oil and grease resistant palm

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Dry environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Fine assembly, assembly, machine operating, building and construction, carpentry, installation work, hvac installation, engineering, transport work, machine driving, warehouse work, airport work, repair work, service work, shop work

PRIMARY INDUSTRIES OF USE

Machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK

Light weight

SPECIFICATION

TYPE Heat protection gloves, Precision work gloves
CATEGORY Cat. II
COLLECTION Infinity
LINING MATERIAL 18 gg, Nylon
LENGTH 215-275 mm
DEXTERITY 5
GRIP DESIGN Foam grip pattern
COLOUR Black, Yellow
PAIRS PER: BUNDLE/CARTON 6/120
DISPLAY TYPE Bulk pack
DIPPING Palm-dipped, Double-dipped
DIPPING MATERIAL Nitrile, Nitrile foam, Waterbased PU
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
INNER MATERIAL SPECIFICATION Nylon, Natural latex
OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE

CE Cat. II

UKCA Cat. II

EAC

TP TC 019:2011

Information/UIS

EN 407:2020 (No flame protection) X1XXXX

EN 388:2016+A1:2018 4121X

EN ISO 21420:2020

ANSI 3 ABR

OEKO TEX® STANDARD 100 SE 14-214 RISE www.oeko-tex.com

ORIGINAL 04 EXCELLENT 2019 dermatest dermatest-guarantee.de

Contact heat rating valid for palm area only

SIZE		ARTICLE NUMBER	EAN
5	XXS	8802-5	7340118327938
6	XS	8802-6	7340118318844
7	S	8802-7	7340118318851
8	M	8802-8	7340118318868
9	L	8802-9	7340118318875
10	XL	8802-10	7340118318820
11	XXL	8802-11	7340118318837

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.