231 LED Installation Beacon

LED Permanent beacon with M 22 thread for control panel / switch gear programme. Extremly high light intesity. Modern Chip-On-Board technology. High protection rating IP 65 for indoor and outdoor applications.



TECHNICAL SPECIFICATIONS

Dimensions (Diameter x Height):	28.7 mm x 46 mm
Dome:	Polycarbonate, transparent
Fixing :	Installation mounting for Ø 22,5 mm (M 22 x 1,5 mm)
Housing :	ABS/PC-Blend, black
Operating voltage:	24 V =, 115 V ~, 230 V ~
Current consumption:	45 mA at 24 V 15 mA at 115 V 15 mA at 230 V
Starting current:	< 0,5 A at 24 V
Life duration:	up to 100.000 h
Terminal element :	2 wires, c. 115 mm long

231 LED Installation Beacon

LED Permanent beacon with M 22 thread for control panel / switch gear programme. Extremly high light intesity. Modern Chip-On-Board technology. High protection rating IP 65 for indoor and outdoor applications.



ORDER SPECIFICATIONS

	24 V =	115 V ~	240 V ~
red	23110055	23110067	23110068
green	23120055	23120067	23120068
yellow	23130055	23130067	23130068
clear	23140055	23140067	23140068
blue	23150055	23150067	23150068