Date: 11/04/2023

A73.100/S, 0...200°C, L1=250 mmx6mm,

Gas actuated thermometer, stainless steel series

Item number:	48733888
Quantity:	1 pcs.
Order code:	A73.100-C1L-SGD-B0250-ZZZ-Z-Z-HZZ-ZZZZZZ G1 FZZZEVZZIWP-AZ1ZZZZZ2ZZZZ
Overview:	A73.100/S, 0...200°C, L1=250 mmx6mm, G 1/2 B axial laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: A73.100, nominal size 100, location of stem centre back Unit: °C Scale range: 0 °C ... 200 °C Connection design: standard, male thread Process connection: G 1/2 B Stem diameter: 6 mm Insertion length L1: 250 mm Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: axial Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.