Date: 11/04/2023

TSD-30 ; -20 ... +80 °C; one switching output (IO-Link/PNP) + 4...20 mA

Electronic Temperature Switch with Display Model TSD-30

Item number:	48770798
Quantity:	1 pcs.
Order code:	TSD-30-3-CA-M0150-GT1-M4-WW-ZZ W1011TS3-ZZZZZ-S5R-GSFK
Overview:	TSD-30 ; -20 ... +80 °C; one switching output (IO-Link/PNP) + 4...20 mA @ 15...35 V DC; Probe length: 150 mm; G 1/2 A DIN EN ISO 1179-2 (formerly DIN 3852-E) Sealing: NBR circular connector M12x1, 4-pin U+=1, U-=3, S+=2, SP1/IO-Link=4 Approvals: cULus Specifications according to data sheet: TE 67.03
Details:	Electronic Temperature Switch with Display Model TSD-30 Specifications according to data sheet: TE 67.03 Output signal: one switching output (IO-Link/PNP) + 4...20 mA Temperature range: -20 ... +80 °C Probe length unit: mm Process connection: G 1/2 A DIN EN ISO 1179-2 (formerly DIN 3852-E) Sealing: NBR Electrical connection: circular connector M12x1, 4-pin Approvals: cULus Pin assignment: U+=1, U-=3, S+=2, SP1/IO-Link=4 Power supply: 15...35 V DC Probe length: 150 mm

© 2023 - WIKA Instruments s.a.r.l.