Specifications

Eaton EP-400203

Catalog Number: EP-400203

Eaton Moeller series SLC Stack light compact, Green, Yellow, Red, 120 V AC, Pulsed tone, Wall mounting

General specifications

Product Name
Eaton Moeller® series SLC Signal tower compact

Catalog Number
EP-400203

Model Code
SLC-FW-RYG-AP-120

EAN
4015082954871

Product Length/Depth
79 mm

Product Height
237 mm

Product Width
61 mm

Product Weight
0.207 kg

Certifications
CE
IEC/EN 60947-5-1
IEC/EN 60529
UL Category Control No.: NKCR, NKCR7

UL File No.: E29184
UL report applies to both US and Canada

Product specifications

Type

Complete device

Product Category

SL signal towers

Fitted with:

Push-in

Pollution degree

3

Alarm type

Pulsed tone

Connection to SmartWire-DT

No

Mounting Method

Wall

Illumination

Continuous LED
Red blinking LED

Decibel

70 dB

Ambient operating temperature - max

50 °C

Ambient operating temperature - min

-25 °C

Leakage current

0.003 A

Outside diameter

61 mm

Radiation angle

360 °

Rated operational voltage (Ue) - max

120 V

Rated operational voltage (Ue) - min

120 V

Color

Black tube
Green

Resources

Brochures

SL4, SL7, SLC Stack light overview brochure BR047017

SLC Stack Light Compact Flyer sa047011

Declarations of conformity

DA-DC-00004994.pdf

DA-DC-00004998.pdf

Installation instructions

eaton-operating-devices-stacklight-compact-slc-instruction-leaflet-il047032zu.pdf

mCAD model

eaton-slc_fw_ryg-drawing.dwg

eaton-slc-fw-ryg-3d-model.stp

Yellow

Red

Lens color

Green

Yellow

Red

Voltage type

AC

Material

UV Protected material

Mounting position

As required

Degree of protection

IP66

NEMA 4X

Overvoltage category

III

Lifespan, electrical

50,000 h

Light type

Continuous light

Red blinking light

Loudness

70 db

Light modules

LED

Number of modules

1

Rated operational voltage

110/120 V AC ± 10 % (50hz/60Hz)

Terminal capacity

Push-in 6-pole

up to 1,5mm² without plastic collar

up to 0,75mm² with plastic collar

Voltage type of operating voltage

AC

Operating voltage at AC, 50 Hz - min

108 V

Operating voltage at AC, 50 Hz - max

132 V

Operating voltage at AC, 60 Hz - min

108 V

Operating voltage at AC, 60 Hz - max

132 V

Operating voltage at DC - min

0 V

Operating voltage at DC - max

0 V

Color light 1

Green

Color light 2

Yellow

Color light 3

Red

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia