Date: 25/01/2024

432.50.160 100 mbar G1/2B

Diaphragm Pressure Gauges, Process Industry

Item number: 9052526

Quantity: 1 pcs.

Order code: 432.50-ZZZF-MG210Z-GDU-ZZ-CASZZ-ZZZZ 4A 3A3DZFJHZGZZ-IZZZZZZ12ZZZ

Overview:
432.50.160 100 mbar G1/2B
Diaphragm Material: stainless steel
Connector location: lower mount
Sealing of pressure chamber: FPM
Process connection: G 1/2 B
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
class 1.6
Overpressure safety: 5 x Full scale value, max 40 bar
Ingress protection: IP 54
Window: laminated safety glass
Pressure Gauge Standard: International (standard Europe)
WIKA with Serial number

Details:
Diaphragm Pressure Gauges, Process Industry
Model: 432.50
Specifications according to data sheet: PM 04.03
Case filling: without
Case: with pressure blowout disk
Nominal size: 160 mm
Scale range: 0...100 mbar
Process connection: G 1/2 B
Connector location: lower mount
Diaphragm Material: stainless steel
Lower Body Material: Stainless-Steel
Pointer: standard pointer
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Accuracy class: class 1.6
Overpressure safety: 5 x Full scale value, max 40 bar
Case material: Stainless steel 1.4301
Case surface: bare
Ingress protection: IP 54
Sealing of pressure chamber: FPM
Window: laminated safety glass
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
Serial number: with Serial number

© 2024 - WIKA Instruments s.a.r.l.