DATASHEET - IZMX-AS22-16-1

Signalling switch ON-OFF, 2W

Part no. IZMX-AS22-16-1
184172

EL Number (Norway) 4398515

General specifications

Product name	Eaton Moeller series IZMX/INX auxiliary contact block
Part no.	IZMX-AS22-16-1
EAN	4015081783441
Product Length/Depth	100 millimetre
Product height	100 millimetre
Product width	100 millimetre
Product weight	0.068 kilogram
Compliances	RoHS conform
Product Tradename	IZMX/INX
Product Type	Accessories
Product Sub Type	Auxiliary contact block

Delivery program

Type	Accessory
Model	Integrable
Special features	2 changeover contacts Retrofit kit for IZMX16 circuit-breakers The retrofit kit includes the required SEC control cable terminals. The basic device already contains two changeover contacts. Mounting kit with 2 additional changeover contacts with cable lengths for IZMX16.
Used with	INX16... IZMX16...

Technical Data - Electrical

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V	10 A
Rated breaking capacity (inductive load)	10 A (250 V AC) 0.25 A (250 V DC) 0.5 A (125 V DC)
Electric connection type	Flat plug-in connection

Technical Data - Mechanical

Mounting Method	Other
Number of contacts (change-over contacts)	2
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	0
Number of switches (fault signal)	0
Lamp holder	None

Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C

Additional information

Accessory/spare part type	Auxiliary contact

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018])

Number of contacts as change-over contact		2
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of fault-signal switches		0
Rated operation current Ie at AC-15, 230 V	A	10

Type of electric connection			Flat plug-in connection
Model			Integrable
Mounting method			Other
Lamp holder			None

© 04/2023 by Eaton Industries GmbH