Specifications

Eaton 281277

Catalog Number: 281277

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 50A, N1-S50-CNA



General specifications

Product Name
Eaton Moeller series NZM molded case circuit breaker magnetic

Catalog Number
281277

EAN
4015082812775

Product Length/Depth
88 mm

Product Height
165.5 mm

Product Width
90 mm

Product Weight
1.046 kg

Compliances
RoHS conform

Certifications
IEC/EN 60947
CE marking
IEC 60947-2
Specially designed for North America
CSA (File No. 22086)
UL/CSA
CSA certified
UL listed
UL (File No. E31593)
IEC
UL (Category Control Number DKPU2)
CSA-C22.2 No. 5-09
CSA (Class No. 1432-01)
UL 489

Powering Business Worldwide

Product specifications

Type

Circuit breaker

Special features

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)
Rated current = rated uninterrupted current: 50 A
Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate.
Motor protection in conjunction with contactor and overload relay
With short-circuit release
Without overload release Ir

Application

Branch circuits, feeder circuits
Use in unearthed supply systems at 690 V

Amperage Rating

50 A

Voltage rating

690 V - 690 V

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Characteristic curve

eaton-circuit-breaker-nzm-mccb-characteristic-curve.eps

eaton-circuit-breaker-let-through-current-nzm-mccb-characteristic-curve-002.eps

eaton-circuit-breaker-nzm-mccb-characteristic-curve-058.eps

Declarations of conformity

DA-DC-03_N1

Drawings

eaton-circuit-breaker-nzm-mccb-dimensions-017.eps

eaton-circuit-breaker-switch-nzm-mccb-dimensions-014.eps

eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-006.eps

eCAD model

ETN.281277.edz

Installation instructions

eaton-cirucit-breaker-switch-disconnector-nzmb-il01203004z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CS-nzm1_3p

DA-CD-nzm1_3p

Technical data sheets

eaton-nzm-technical-information-sheet

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Pollution degree

3

Mounting Method

Fixed

Built-in device fixed built-in technique

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Equipment heat dissipation, current-dependent

4.22 W

Utilization category

A (IEC/EN 60947-2)

Isolation

300 V AC (between the auxiliary contacts)

500 V AC (between auxiliary contacts and main contacts)

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

70 °C

Ambient storage temperature - min

40 °C

Low-voltage HBC fuse - max

200 A gG/gL

Protection against direct contact

Finger and back-of-hand proof to VDE 0106 part 100

Rated insulation voltage (Ui)

690 V

Rated operating power at AC-3, 230 V

15 kW

Rated operating power at AC-3, 400 V

22 kW

Switch off technique

Magnetic

Degree of protection

IP20 (basic degree of protection, in the operating controls area)

IP20

Direction of incoming supply

As required

Electrical connection type of main circuit

Other

Lifespan, mechanical

20000 operations

Overvoltage category

III

Rated operational current

50 A (660-690 V AC-3, making and breaking capacity)

160 A (400 V AC-1, making and breaking capacity)

125 A (415 V AC-1, making and breaking capacity)

50 A (690 V AC-1, making and breaking capacity)

Degree of protection (IP), front side

IP40 (with insulating surround)

IP66 (with door coupling rotary handle)

Degree of protection (terminations)

IP10 (tunnel terminal)

IP00 (terminations, phase isolator and strip terminal)

Number of poles

Three-pole

Terminal capacity (copper strip)

Max. 9 segments of 9 mm x 0.8 mm at box terminal

Min. 2 segments of 9 mm x 0.8 mm at box terminal

Lifespan, electrical

5000 operations at 690 V AC-3

7500 operations at 400 V AC-3

7500 operations at 415 V AC-3

Functions

Short-circuit protection

Shock resistance

20 g (half-sinusoidal shock 20 ms)

Rated operational current for specified heat dissipation (In)

50 A

Short-circuit release non-delayed setting - max

700 A

Short-circuit release non-delayed setting - min

400 A

Handle type

Rocker lever

Instantaneous current setting (Ii) - max

700 A

Instantaneous current setting (Ii) - min

400 A

Number of operations per hour - max

120

Overload current setting (Ir) - max

0 A

Overload current setting (Ir) - min

0 A

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz

85 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz

35 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz

35 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz

10 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz

7.5 kA

Standard terminals

Box terminal

Rated operating voltage Ue (UL) - max

480 Y / 277 V

Release system

Thermomagnetic release

Short-circuit total breaktime

< 10 ms

Terminal capacity (aluminum solid conductor/cable)

16 mm² (1x) at tunnel terminal

Terminal capacity (control cable)

14 mm² - 18 mm² (1x)

16 mm² - 18 mm² (2x)

Terminal capacity (copper busbar)

Min. 12 mm x 5 mm direct at switch rear-side connection

Max. 16 mm x 5 mm direct at switch rear-side connection

M8 at rear-side screw connection

Terminal capacity (copper solid conductor/cable)

6 mm² - 12 mm² (1x) direct at switch rear-side connection

6 mm² - 12 mm² (1x) at box terminal

6 mm² - 9 mm² (2x) direct at switch rear-side connection

16 mm² - 95 mm² (1x) at tunnel terminal

Terminal capacity (copper stranded conductor/cable)

4 mm² - 3/0 mm² (1x) at tunnel terminal

25 mm² (2x) at box terminal

25 mm² - 70 mm² (1x) at box terminal

4 mm² - 2/0 mm² (1x) direct at switch rear-side connection

Rated short-circuit breaking capacity Icu (IEC/EN 60947) at 400/415 V, 50/60 Hz

35 kA

Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz

105 kA

Rated short-circuit making capacity Icm at 440 V, 50/60 Hz

74 kA

Rated short-circuit making capacity Icm at 525 V, 50/60 Hz

40 kA

Rated short-circuit making capacity Icm at 690 V, 50/60 Hz

17 kA

Rated short-circuit making capacity Icm at 240 V, 50/60 Hz

187 kA

Rated impulse withstand voltage (Uimp) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Uimp) at main contacts

6000 V

Power loss

4.2 W



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia