Date: 12/04/2023

OLS-c51, G 1/2", Opened in media (SPST n.c.), 2 meter

OLS-c51, G 1/2", Opened in media (SPST n.c.), 2 meter

Item number: 14243207

Quantity: 1 pcs.

Order code: OLS-C51-G1Z-CNCK3-M0002-AZ W101OL51O1LB

Overview:
OLS-c51, G 1/2", Opened in media (SPST n.c.), 2 meter
Optoelectronic level switch, intrinsically safe
Approvals: Ex approved model OPG051
Process connection: G 1/2"
Output Signal: 4 / 20 mA
Switch function: Opened in media (SPST n.c.)
Power supply: 7.5 - 30 V DC
Electrical connection: Cable PUR
pin assignment el. connection: 1 = U+, 2 =U-
Unit cable length: meter
Cable length: 2
Operating pressure: max. 40 bar
Media temperature: -30…135 °C
Wetted parts: Stainless steel 1.4571, borosilicate glass, epoxide resin
Approval: ATEX/IECEx
Approval marking: ATEX/IECEx - II 1/2 G Ex ia IIC T4 Ga/Gb
Certificate: ATEX EPS 13 ATEX 1 567 X
Specifications according to data sheet: LM 31.04

Details:
OLS-c51, G 1/2", Opened in media (SPST n.c.), 2 meter
Optoelectronic level switch, intrinsically safe
Approvals: Ex approved model OPG051
Process connection: G 1/2"
Output Signal: 4 / 20 mA
Switch function: Opened in media (SPST n.c.)
Power supply: 7.5 - 30 V DC
Electrical connection: Cable PUR
pin assignment el. connection: 1 = U+, 2 =U-
Unit cable length: meter
Cable length: 2
Operating pressure: max. 40 bar
Media temperature: -30…135 °C
Wetted parts: Stainless steel 1.4571, borosilicate glass, epoxide resin
Approval: ATEX/IECEx
Approval marking: ATEX/IECEx - II 1/2 G Ex ia IIC T4 Ga/Gb
Certificate: ATEX EPS 13 ATEX 1 567 X
Specifications according to data sheet: LM 31.04

© 2023 - WIKA Instruments s.a.r.l.