PRODUCT-DETAILS

OT400DFCC3T

OT400DFCC3T Safety switch



General Information

Extended Product Type	OT400DFCC3T
Product ID	1SCA022277R0490
EAN	6417019063331
Catalog Description	OT400DFCC3T Safety switch
Long Description	Safety switch, 3-p. 415V AC23 400A, 220kW. Mounted auxiliary contact: 2NO1NC. Plastic enclosure. IP65. Black Pistol handle. Interlocked cover. Defeatable interlocking. The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. PE terminals included.

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
RoHS Declaration	1SCC340075D0201

© 2025 ABB. All rights reserved.

RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	3fba797c-37e6-485d-b2b9-f5c5f3da3053 Finland
Simplified SCIP	a896705e-e89d-4fc2-bb45-cfbbc2113123 Germany 33a6131a-e412-4906-9093-8771f82a16ad Norway 7fb0dc93-bb96-4040-b7c4-837652850a61 Hungary a82183b5-3266-40bb-bf6a-9251aa17685c Estonia 57074bea-f833-4840-bc68-c5358a56c807 Croatia 2893db37-5192-4f7f-a276-0d49edfd0770 Greece b0d84869-240b-4e49-9299-737d45a92fc2 Netherlands d19a2106-89df-4f74-a127-7cfc8df8783f Czech Republic 3280c8f3-d8da-4a76-8813-9f7e2d6c07db Poland 5271e441-926b-4137-b18e-0ce9d111a5a8 France 76e54d9c-8006-4d81-a020-11e57d0b6c87 Spain 93ecc24a-8def-407f-96a7-72832c1fa7b4 Bulgaria 85b2da21-bced-4da6-9556-992e76a3930f Portugal 4409a7ce-e86a-4c14-ba07-facd2ace16cf Hungary aedc0196-a7cc-438d-9f3f-a645daf4eefc Germany e260ac80-7e59-49cc-9b9d-8c55f42c30bd Italy 9436fe95-b05b-429d-aa03-46691a60af94 Belgium d7851f1e-3cf0-40a2-863b-16db9a625fc2 Poland d5707dbe-e48a-4228-8e1c-ba3bef8426c6 Sweden 3693534e-1859-49dd-9348-305e8b34da63 Belgium f01840e2-f478-484d-8e61-69cf2c7aee89 Germany 97f5e049-7983-4db7-aaaf-aa5028f0ba2a Poland 778cddd3-5549-40fc-9a47-31cfa3070ab5 Germany 5dc70f57-00f6-4cb8-992f-c75e6d068cfa Germany b0d0dc25-afdb-4ca6-a720-b84be62f8392 Denmark 9018717d-cdfb-4d01-8e80-d58ad97f8f9c France 11889ba3-7b24-4c7a-8a35-cfff3f1e49b2 Sweden
Toxic Substances Control Act - TSCA	1SCC340095D0201

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340015M0004

Environmental

Degree of Protection	acc. to IEC 60529 IP65
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country or Territory of Origin	Finland

Dimensions

Product Net Width	380 mm
Product Net Height	840 mm
Product Net Depth / Length	180 mm
Product Net Weight	14.206 kg

© 2025 ABB. All rights reserved.

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	415 mm
Package Level 1 Depth / Length	910 mm
Package Level 1 Height	325 mm
Package Level 1 Gross Weight	16.4 kg
Package Level 1 EAN	6417019063331

Technical

Cable Entry Position	Top/Bottom
Cable Outlets Per Side	II-flange / II-flange
Color	RAL7035
Connecting Capacity Main Circuit	Hole Diameter 10 mm Screw Clamp / PE Terminal 4pc,25 ... 120 mm^2
Conventional Thermal Current (I_{the})	Fully Enclosed 400 A
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Handle Color	Black
Handle Type	Pistol handle
Impact Resistance Rating	Housing IK08
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	2 NO, 1 NC
Neutral Type	No Neutral Terminal
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	2
Number of Poles	3P
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out
Power Loss	at Rated Operating Conditions per Pole 10 W
Rated Conditional Short-Circuit Current (I_{nc})	61.5 kA
Rated Insulation Voltage (U_i)	750 V
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 220 kW (500 V) 280 kW (690 V) 355 kW
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V AC) 65 kA
Rated Short-time	for 1 s 15 kA

© 2025 ABB. All rights reserved.

Withstand Current Low Voltage (I_{cw})	
Recommended Screw Driver	Main Circuit M10
Standards	IEC 60947-1, -3
Tightening Torque	Main Circuit 44 N·m

Technical UL/CSA

Recommended Screw Driver	Main Circuit M10
Tightening Torque	Main Circuit 44 N·m

Certificates and Declarations

Declaration of Conformity - CE	1SCC340025D2704

External Classifications and Standards

Object Classification Code	Q
ETIM 9	EC000216 - Switch disconnector (low voltage)
ETIM 10	EC000216 - Switch disconnector (AC)
UNSPSC	39122205
IDEA Granular Category Code (IGCC)	5166 >> Safety switch
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3642416
E-Number (Norway)	1429312
E-Number (Sweden)	3140234

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

© 2025 ABB. All rights reserved.





© 2025 ABB. All rights reserved.