

# 3313
# DOUBLE FEMALE MANIFOLD BSP PARALLEL

**Description**
**Dimensions**
**Specifications**
**CAD drawings**
**Related products**

| | | | |
|---|---|---|---|
| **maximum working pressure** | **bar**<br>20 | **MPa**<br>2 | **psi**<br>290 |
| **working temperature** | **°C (Celsius)**<br>From -10 to 80 | **F (Farenheit)**<br>From 14 to 176 | **K (Kelvin)**<br>From 263 to 353 |
| **body** | anodized aluminium | | |




# 3313

# DOUBLE FEMALE MANIFOLD BSP PARALLEL

Zoom

Description
Dimensions
Specifications
CAD drawings
Related products

convert weight standard : kg | oz

convert dimensions : mm | inch

| legris connectic | C1 | C2 | H (mm) | H1 (mm) | H2 (mm) | K (mm) | L (mm) | L1 (mm) | L2 (mm) | L3 (mm) | M (mm) | ØT (mm) | (kg) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 3313 10 13 02 | G1/4 | G1/8 | 4,5 | 30,0 | 15,0 | 15,5 | 61,0 | 20,0 | 5,5 | 50,0 | 30,0 | 5,0 | 0,075 |
| 3313 10 13 03 | G1/4 | G1/8 | 4,5 | 30,0 | 15,0 | 15,5 | 91,0 | 20,0 | 30,5 | 30,0 | 30,0 | 5,0 | 0,115 |
| 3313 10 13 04 | G1/4 | G1/8 | 4,5 | 30,0 | 15,0 | 15,5 | 121,0 | 20,0 | 30,5 | 60,0 | 30,0 | 5,0 | 0,151 |
| 3313 10 13 05 | G1/4 | G1/8 | 4,5 | 30,0 | 15,0 | 15,5 | 151,0 | 20,0 | 30,5 | 90,0 | 30,0 | 5,0 | 0,194 |
| 3313 13 17 02 | G3/8 | G1/4 | 6,0 | 40,0 | 20,0 | 19,0 | 74,0 | 20,0 | 6,5 | 61,0 | 36,0 | 6,5 | 0,109 |
| 3313 13 17 03 | G3/8 | G1/4 | 6,0 | 40,0 | 20,0 | 19,0 | 110,0 | 20,0 | 37,0 | 36,0 | 36,0 | 6,5 | 0,169 |
| 3313 13 17 04 | G3/8 | G1/4 | 6,0 | 40,0 | 20,0 | 19,0 | 146,0 | 20,0 | 37,0 | 72,0 | 36,0 | 6,5 | 0,230 |
| 3313 13 17 05 | G3/8 | G1/4 | 6,0 | 40,0 | 20,0 | 19,0 | 182,0 | 20,0 | 37,0 | 108,0 | 36,0 | 6,5 | 0,286 |
| 3313 13 21 03 | G1/2 | G1/4 | 6,0 | 40,0 | 20,0 | 22,0 | 116,0 | 28,0 | 40,0 | 36,0 | 36,0 | 6,5 | 0,222 |
| 3313 13 21 04 | G1/2 | G1/4 | 6,0 | 40,0 | 20,0 | 22,0 | 152,0 | 28,0 | 40,0 | 72,0 | 36,0 | 6,5 | 0,295 |
| 3313 13 21 05 | G1/2 | G1/4 | 6,0 | 40,0 | 20,0 | 22,0 | 188,0 | 28,0 | 40,0 | 108,0 | 36,0 | 6,5 | 0,369 |