PRODUCT-DETAILS

E6.2H 6300 Ekip Hi-Touch LSI 3p F HR

E6.2H 6300 Ekip Hi-Touch LSI 3p F HR



General Information

Extended Product Type	E6.2H 6300 Ekip Hi-Touch LSI 3p F HR
Product ID	1SDA071298R1
EAN	8015644751487
Catalog Description	E6.2H 6300 Ekip Hi-Touch LSI 3p F HR
Long Description	C.BREAKER SACE EMAX2 E6.2H 6300 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/HI-TOUCH-LSI R 6300 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
Environmental Product Declaration - EPD	9AKK108468A1905 9AKK108468A1913

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

© 2024 ABB. All rights reserved.

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	fa293613-5289-4323-992b-fc179ece25bc Italy (IT)
Simplified SCIP	24f3e458-292b-4b28-abba-229e3b698125 Germany (DE) 4a35c4d8-f0cb-4873-a676-f035505cfcc3 Hungary (HU) a0af51c8-04ee-4160-a8d5-dd21c760d2ae Belgium (BE) 8f6a7baf-1f58-40b6-b1d7-dec57f860ec9 Spain (ES) eb8d5c5e-7643-4601-b4a8-b3344a28af41 Germany (DE) ae2c524a-98a7-4405-9816-76b6aa467c38 Germany (DE) 5478c353-f26e-4ff9-a3f8-4cff847640ef Croatia (HR) 9a5c5a5c-cad0-41fe-a749-48a5c983efaa Bulgaria (BG) ad6fb889-5f29-4611-9d43-edc609981dcd France (FR) a38dd5b6-6049-4f83-b68e-fd067679613b Sweden (SE) deb5017d-cd9d-4706-9156-c0b0a456c62d Belgium (BE) 26287913-5cc1-4e91-b8dd-ee80a4d32d96 Estonia (EE) aec9a7e7-b78c-42ce-99cc-d1ef57532cd7 Netherlands (NL) 6530e613-8151-4076-acc9-03040dbc6c81 Finland (FI) 379383bd-ec0d-4ab7-b5eb-eeea3398f209 France (FR) 4910da71-fb49-41f2-83a7-83b81f54325d Greece (GR) b69134df-cc20-4e66-84df-8f06eb09370a Germany (DE) e0631034-64a1-4bb0-8227-8b69b757fddd Denmark (DK) 52744f5d-44ee-49a1-a017-763d2ce2a90a Germany (DE) 2e55ddb1-0760-467f-bb93-bdcbb9fd122e Hungary (HU) 03bcc6ac-df4c-4980-a56d-f919cc63a7aa Poland (PL) c4810516-40d5-4860-91c1-f9c583883500 Norway (NO) d6b1e513-0939-4e0e-8245-45882a820f5b Poland (PL) bc597603-a7ef-4463-8711-b906ffc2dfde Poland (PL) 75645da3-15d8-4e7e-abbf-94d2d00bf177 Czech Republic (CZ) 6c5f903b-ef1d-4913-b7d0-d9740977e879 Portugal (PT) 371ca3d8-ce3b-404c-ae49-55c6db710fa3 Sweden (SE)

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	Z6HYETBJ200A000000XX
EAN	8015644751487
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	762 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	109 kg

Container Information

Package Level 1 Units	box 1 piece

© 2024 ABB. All rights reserved.

Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Gross Weight	118 kg
Package Level 1 EAN	8015644751487

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH001252R0223

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 2000 cycle Ue = 500 ... 690 V 2000 cycle 10 cycles per hour
Mechanical Durability	12000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	767 W
Rated Current (I_n)	6300 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 100 kA for 3 s 100 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (525 V AC) 100 kA (690 V AC) 100 kA
Rated Uninterrupted Current (I_u)	6300 A
Rated Voltage (U_r)	690 V
Recommended Screw	Main Circuit M12

© 2024 ABB. All rights reserved.

Driver	
Release	Ekip Hi-Touch LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E6.2
Suitable for IT Networks	Yes, 690V
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5544
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001060R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.