Specifications

Eaton 102440



Catalog Number: 102440

Eaton xEnergy Basic LV systems Low voltage switchgear. Glass door, for HxW=2060x600mm, Clip-down-handle

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	102440
EAN	**Product Length/Depth**
4015081023288	45 mm
Product Height	**Product Width**
2010 mm	615 mm
Product Weight	**Compliances**
7.3 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Accessory
Floor-standing enclosure
Accessory consideration
Service distribution board IVS

Special features

Can be used as left door for two-leaf versions
Transparent doors
Single wing door
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock
Transparent panels from 4 mm safety glass (EN 12150-1, DIN 1249)
Left door for two-section design with 1200 mm enclosure widths

Type

Additional equipment for floor-standing service distribution board IVS

Features

Version as glazed door
EMC-version

Accessory/spare part type

Doors

Surface finishing

Powder coating
With powder coating

Color

Light gray (RAL 7035)
Gray

Degree of protection

IP30
NEMA Other

Unit type

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Modular system

Suitable for height

2060 mm

Suitable for width

600 mm

Cover/door color

Transparent

Cover/door type

Rotary lever

Material

Steel

Sheet steel/glass

Housing material

Sheet steel/glass

Model

Stop door

Mounting method

Floor standing distribution board

Functions

Floor-standing enclosure

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia