Specifications

Eaton 044879



Catalog Number: 044879

Eaton xEnergy Safety Ci LV systems LV switchgear. Flange, through-hole foam rubber, IP54, HxWxD=116x329x23mm

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Safety Ci flange plate	044879
EAN	**Product Length/Depth**
4015080448792	115 mm
Product Height	**Product Width**
23 mm	330 mm
Product Weight	**Compliances**
0.344 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

NYY, NYM 4 x 10 mm² - 4 x 50 mm²
NYY, NYM 4 x 4 mm² - 5 x 10 mm²
375 mm (enclosure dimensions)
NYY, NYM 3 x 1.5 mm² - 5 x 2.5 mm²
Accessory for basic enclosures
Basic enclosure
xEnergy Safety Ci

Type

Accessory for basic enclosures
Basic enclosure
xEnergy Safety Ci

Features

Pre-stamping

Accessory/spare part type

Sponge-rubber flange IP54

Unit type

Modular system

Number of connector holes

0

Suitable for nominal thread (PG) - max

30

Suitable for nominal thread (PG) - min

10

Degree of protection

IP54
Other

Surface protection

Untreated

Outer cable diameter

2 x (20 - 30) mm
4 x (15 - 19) mm
42 x (10 - 13) mm

Shape

Straight

Material

Plastic

Resources

Brochures

eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

Catalogs

eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf

Drawings

eaton-enclosures-flanges-xeffect-ci-enclosure-dimensions-003.eps

eaton-enclosures-flange-xenergy-safety-ci-flange-plate-symbol.eps

Installation instructions

IL0566

mCAD model

fl4_d.dwg

fl4_d.stp

Model

Cable screw gland

Thread type

None

Thickness

4 mm

Suitable for cable diameter - max

30 mm

Suitable for cable diameter - min

10 mm

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia