domestic fuse carriers


058 11


058 14


058 21


058 24

Dimensions (p. 183)

With label-holders
With insulated carrier class II, padlockable
Coupling via supply busbars
Shielded terminals capacity 2 x 10 mm²
Possibilty to signal indicator blown fuse
Fuse not supplied

For domestic cylindrical cartridge fuses

Conform to EN 60269-1 and IEC 60269-1,3

Single pole

Pack	Cat.Nos	For domestic cartridges	Cartridge dimensions (mm)	Number of modules
10	058 10	10 A - 230 V~	8.5 x 23	1
10	058 11	16 A	10.3 x 25.8	1
10	058 12	20 A - 400 V~	8.5 x 31.5	1
10	058 13	25 A	10.3 x 31.5	1
10	058 14	32 A	10.3 x 38	1

Single pole + neutral

10	058 20	10 A - 230 V~	8.5 x 23	1
10	058 21	16 A	10.3 x 25.8	1
10	058 22	20 A - 400 V~	8.5 x 31.5	1
10	058 23	25 A	10.3 x 31.5	1
10	058 24	32 A	10.3 x 38	1

For miniature cylindrical cartridge fuses

Conform to EN 60127-6 and IEC 60127-6
To protect sensitive equipment: transformers, electronic equipment, etc.

Single pole

Pack	Cat.Nos	Cartridge dimensions (mm)	Voltage	Number of modules
5	058 00	5 x 20	250 V~	1

Single pole + neutral

5	058 02	5 x 20	250 V~	1

Supply busbars (p. 249)

domestic cartridge fuses


102 63


103 06


113 10


117 16


124 20


126 25


134 32

Miniature type 5 x 20

Instant reaction fuse - Ceramic body
Conform to EN/IEC 60127-2
High rupture capacity (A)

For use with dimmers, Viking terminal blocks and emergency lightning units, transformers

Pack	Cat.Nos	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)
10	102 02	0.2		
10	102 05	0.5		
10	102 06	0.63		
10	102 10	1		
10	102 20	2	250	1500
10	102 30	3.15		
10	102 50	5		
10	102 63	6.3		
10	102 96(1)	10	250	500

Cylindrical

Pack	Cat.Nos Without indicator	Cat.Nos With indicator	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps) Copper	Protected section (mm²)	Color Indication
			6.3 x 23				
10	103 06(2)		6	230	6000	1.5	
			8.5 x 23				
10		114 06	6	230	6000		
10/**100**	113 10	114 10	10			1.5	
			10.3 x 25.8				
10	116 10(2)		10	230	6000		
10	116 16(2)	117 16(2)	16			2.5	
			8.5 x 31.5				
10/**100**	123 20	124 20	20	400	20000	2.5	
			10.3 x 31.5				
10	126 16		16				
10	126 20		20	400	20000		
10	126 25	127 25	25			4	
			10.3 x 38				
10/**100**	133 32		32	400	20000		
10		134 32	32			6	

Neutral links

Pack	Cat.Nos	
10	123 00	8 x 32 (previously 8.5 x 31.5)
10	133 00	10 x 38

Other cartridge fuses (p. 132)

Legrand System
These products are part of protection and distribution systems > See p. 142-143

(1) Overrating not described by standarts
(2) Conform to BS 1361 (1971)

Bold pack quantities: Minimum quantities to be ordered