Specifications

Eaton EBH000O3TS5

Catalog Number: EBH000O3TS5

Eaton Bussmann series low voltage NH fuse base, Switch disconnector, low voltage, 160 A, AC 690 V, NH000, AC21B, 3P, IEC, plate mounting, for connection of round conductors - S-bridge clamps



General specifications

Product Name Eaton Bussmann series low voltage NH fuse base	**Catalog Number** EBH000O3TS5
	EAN 5027590335850
Product Length/Depth 110 mm	**Product Height** 200 mm
Product Width 95 mm	**Product Weight** 574 g
Compliances CE	**Certifications** IEC/EN 60947-1 IEC 60947-3

Powering Business Worldwide

Product specifications

Type

Fuse accessory

Application

Motor control centres, distribution boards, Cable distribution cabinets

Amperage Rating

160 A

Rated operational power at AC-23A, 400 V, 50 Hz

0.064 kW

Rated permanent current (Iu)

160 A

Rated uninterrupted current (Iu)

160 A

Conditioned rated short-circuit current Iq

0.1 kA

With error protection

No

Number of poles

Three-pole

Rated operation power at AC-23, 400 V

0.064 kW

Rated short-time withstand current (Icw)

100 kA

Electrical connection type of main circuit

Cable clamp

Actuator position

Front side

Actuator type

Cover grip

Construction size

NH000

Fuse shape

Horizontal

Suitable for

Front mounting

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

UKCA fuse switch disconnectors, EBC, EBV and EBH series

CE fuse switch disconnectors, EBC, EBV and EBH series

Technical data sheets

10275 EBV Vertical fuse switch-disconnector

10292 EBH000 Horizontal switch-disconnector

Technical service bulletins

10293 EBH Horizontal switch-disconnector

NH000

Suitable for fuses

NH000

Cable entry type

Other

Mounting method

DIN rail

60 mm busbar mounting

Voltage rating

690

Degree of protection (front side)

IP30

Electrical connection type

Cable clamp

Rated operating voltage (Ue) at AC - max

690 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia