Date: 24/04/2023

233.30.063 10 bar G1/4B lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number:	9020560
Quantity:	1 pcs.
Order code:	233.30-C-BG410Z-GB-UZEZCZZ-ZZZZZZZ 313D4AZIYG0 Z2Z-IZZZZZZ121ZZ LABEL-PG1DE-ZZZZZ
Overview:	233.30.063 10 bar G1/4B lower mount Measuring System 316 SS Ingress protection: IP 65 class 1.6 Window: polycarbonate Case filling fluid: glycerine Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 … +60 °C Pressure Gauge Standard: International (standard Europe) stop-pin at zero *WIKA* with Serial number Label: WIKA standard without / with Tag-number
Details:	Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 233.30 Specifications according to data sheet: PM 02.04 Measuring system: stainless steel Case filling: with Nominal size: 063 mm Measuring range: gauge pressure range Scale range: 0...10 bar Process connection: G 1/4 B Connector location: lower mount Window: polycarbonate Pointer: standard pointer Accuracy class: class 1.6 Material pressure element: Measuring System 316 SS Case filling fluid: glycerine 99.7% Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* stop pin on dial: at zero Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 233.30 Specifications according to data sheet: PM 02.04

© 2023 - WIKA Instruments s.a.r.l.

Measuring system: stainless steel
Case filling: with
Nominal size: 063 mm
Measuring range: gauge pressure range
Scale range: 0...10 bar
Process connection: G 1/4 B
Connector location: lower mount
Window: polycarbonate
Pointer: standard pointer
Accuracy class: class 1.6
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316 SS
Case filling fluid: glycerine
Ingress protection: IP 65
Permissible medium temperature: + 100 °C
Permissible ambient temperature: -20 … +60 °C
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
stop pin on dial: at zero
with Serial number
Permissible ambient temperature: -20 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.