Date: 11/04/2023

TR34, PT100-2w, cl.B, 1/2 NPT fixed, 50 mm x 6 mm

TR34 Miniature resistance thermometer, explosion protected version, thread-mounted

Item number:	48789655		
Quantity:	1 pcs.		
Order code:	TR34-B-P2-ZLZZZZ-1560050-ZZZ-7ZZ-ZZZ	R34	0069ZPZZZZWIKA0Z
Overview:	TR34, PT100-2w, cl.B, 1/2 NPT fixed, 50 mm x 6 mm ATEX / IECEx Output signal: PT100-2w, cl.B Electrical connection: Circular connector, M12x1 Process connection: Fixed threaded hex bushing 1/2 NPT Process temperature: -50 ... +150°C Sensor diameter ød: 6 mm Insertion length A: 50 mm Permissible ambient temperature: -50 ... +85 °C (-58 ... +185 °F) Pin assignment: Standard pin connection Pt-Sensors (see datasheet) Specifications according to data sheet: TE 60.34		
Details:	TR34 Miniature resistance thermometer, explosion protected version, thread-mounted Specifications according to data sheet: TE 60.34 Electrical connection: Circular connector, M12x1 Approvals: ATEX / IECEx Output signal: Pt100 Class B (IEC 60751), 2-wire Process temperature: -50 ... +150°C Process connection: Fixed threaded hex bushing 1/2 NPT Sensor diameter ød: 6 mm Insertion length A: 50 mm Permissible ambient temperature: -50 ... +85 °C (-58 ... +185 °F) Pin assignment: Standard pin connection Pt-Sensors (see datasheet)		

© 2023 - WIKA Instruments s.a.r.l.