Specifications

Eaton 120644

Catalog Number: 120644

Eaton Moeller series xEffect - FAZ-NA-DC MCB. FAZ-DC, 2-pole, C, 16 A, rated switching capacity acc. to IEC/EN 60947-2: 10 kA, UL



General specifications

Product Name
Eaton Moeller series xEffect - FAZ-NA-DC MCB

Catalog Number
120644

EAN
4015081184743

Product Length/Depth
105 mm

Product Height
75.5 mm

Product Width
35.4 mm

Product Weight
0.243 kg

Compliances
RoHS conform

Certifications
IEC 60947-2
UL 489, CSA C22.2 No. 5
EN45545-2
IEC 61373

Powering Business Worldwide

Delivery program

Application

Switchgear for export to North America (UL-listed)

Number of poles

Two-pole

Number of poles (total)

2

Number of poles (protected)

2

Tripping characteristic

C

Release characteristic

C

Amperage Rating

16 A

Type

FAZ-DC

Miniature circuit breaker

Technical data - electrical

Voltage type

DC

Voltage rating at DC

500 V DC

Rated operational voltage (Ue) - max

250 V

Rated insulation voltage (Ui)

440 V

Rated impulse withstand voltage (Uimp)

4 kV

Frequency rating - min

50 Hz

Frequency rating - max

60 Hz

Rated switching capacity (IEC/EN 60947-2)

10 kA

Rated short-circuit breaking capacity (EN 60898) at 230 V

0 kA

Rated short-circuit breaking capacity (EN 60898) at 400 V

0 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 230 V

10 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 400 V

10 kA

Overvoltage category

III

Pollution degree

2

Technical data - mechanical

Width in number of modular spacings

2

Built-in depth

70.5 mm

Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In)

16 A

Heat dissipation per pole, current-dependent

0 W

Degree of protection

IP20

Connectable conductor cross section (solid-core) - min

1 mm²

Connectable conductor cross section (solid-core) - max

25 mm²

Connectable conductor cross section (multi-wired) - min

1 mm²

Connectable conductor cross section (multi-wired) - max

25 mm²

Equipment heat dissipation, current-dependent

4.3 W

Static heat dissipation, non-current-dependent

0 W

Heat dissipation capacity

0 W

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

75 °C

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Additional information

Current limiting class

3

Features

Additional equipment possible

Special features

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

Used with

Miniature circuit breaker

FAZ-DC

Resources

Application notes

eaton-maximum-cable-lengths-for-eatons-protective-devices-brochure-br034006en-en-us.pdf

Brochures

eaton-pdd-railrolling-stock-brochure-br011002en-en-us.pdf

Catalogs

eaton-xeffect-faz-na-dc-mcb-catalog-ca003033en-en-us.pdf

Characteristic curve

eaton-xeffect-faz-na-dc-mcb-characteristic-curve.jpg

Declarations of conformity

DA-DC-03_FAZ-DC

DA-DC-03_FAZ-B-C-D

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

DA-DC-03_FAZ-NA-DC

Drawings

eaton-xeffect-faz-dc-mcb-dimensions-004.jpg

eaton-mcb-xeffect-faz-na,-3d-drawing-003.eps

eCAD model

ETN.FAZ-C16_2-NA-DC.edz

Installation instructions

IL019137ZU

mCAD model

eaton-faz_mcb_2p_na_dc-3d-model.stp

eaton-faz_mcb_2p_na_dc-drawing.dwg

Wiring diagrams

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia