Date: 12/04/2023

PCA2MA 4 … 25 bar Adaptor 1/2 NPT-F , 1/2 -14 NPT-F

pca2MA 4/25bar

Item number: 48052329

Quantity: 1 pcs.

Order code: PCA2MA-BAFC-3ASZZZ1ZZ CZKW
B000450DZZZZZZZZ
F4-C5- - - - -

Overview:
PCA2MA 4 … 25 bar Adaptor 1/2 NPT-F , 1/2 -14 NPT-F
Compact pressure switch, flameproof Enclosure Ex d PCA
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
4 … 25 bar, working range -1 … 25 bar, proof pressure 60 bar
Process connection: Adaptor 1/2 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range

1. set point: 4.50 bar decreasing,

Approvals / Certificates
IECEx-ATEX Ex d

Details:
pca2MA 4/25bar
PCA2MA 4/25bar
process connection: 1/2 NPT female
cable entry : 1/2 NPT female
Eex d IIC T6

setting point at 4,5 bar decrease
Compact pressure switch, flameproof Enclosure Ex d
Model PCA
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM
1xSPDT, silver contact
4 … 25 bar, working range -1 … 25 bar, proof pressure 60 bar
Process connection: Adaptor 1/2 NPT-F

© 2023 - WIKA Instruments s.a.r.l.

Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCA2MA 4 … 25 bar
1. set point: 4.50 bar decreasing,

Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.