PRODUCT-DETAILS

E1.2N 800 Ekip G Touch LSIG 3p WMP

E1.2N 800 Ekip G Touch LSIG 3p WMP



General Information

Extended Product Type	E1.2N 800 Ekip G Touch LSIG 3p WMP
Product ID	1SDA072117R1
EAN	8015644759674
Catalog Description	E1.2N 800 Ekip G Touch LSIG 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E1.2N 800 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/G/TOUCH-LSIG R 800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
Environmental Product Declaration - EPD	9AKK108468A1900 9AKK108468A3028

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

© 2024 ABB. All rights reserved.

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	Z1NPEFAN200A000000XX
EAN	8015644759674
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	278 mm
Product Net Height	363.5 mm
Product Net Depth / Length	271 mm
Product Net Weight	18 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	20 kg
Package Level 1 EAN	8015644759674

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 8000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle

© 2024 ABB. All rights reserved.

	60 cycles per hour
Number of Poles	3P
Power Loss	100 W
Rated Current (I_n)	800 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 50 kA (660 V AC) 50 kA (690 V AC) 50 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 50 kA for 3 s 30 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 50 kA
Rated Uninterrupted Current (I_u)	800 A
Rated Voltage (U_r)	690 V
Release	Ekip G Touch LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E1.2
Suitable for IT Networks	Yes, 690V

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5546
Instructions and Manuals	1SDH000999R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection

© 2024 ABB. All rights reserved.

IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2






© 2024 ABB. All rights reserved.