Date: 11/04/2023

DA-160UR - 0...4 bar - 2x1/4 -NPT-F - 1/2 -14 NPT-F

Differential pressure switch, flameproof enclosure Ex d

Item number: 48778647

Quantity: 1 pcs.

Order code: DA-160UR-BBHB-BAMZZZAB1ZZ ZCW
F7-C5- - - - -

Overview:
DA-160UR - 0...4 bar - 2x1/4 -NPT-F - 1/2 -14 NPT-F
Differential pressure switch, flameproof enclosure Ex d DA
static and one-side pressure: 160 bar
Contact version: 1x SPDT silver contact, adjustable dead band
setting range: 0...4 bar
Set point definition: Set Point not defined
Process connection: 2x1/4 -NPT-F
Electrical connection: 1/2 -14 NPT-F
Mounting: Enclosure with plate for wall or direct mounting
Diaphragm Material: AISI 304
Brand: WIKA Instruments Italia
Connection: Stainless steel AISI 316L
Specifications according to data sheet: PV 35.43
Repeatability of set point: ≤ 1% of span

Approvals / Certificates
IECEx-ATEX Ex d

Details:
Differential pressure switch, flameproof enclosure Ex d
Models DA and DA10
Specifications according to data sheet: PV 35.43
Repeatability of set point: ≤ 1% of span
static and one-side pressure: 160 bar
Contact version: 1x SPDT silver contact, adjustable dead band
setting range: 0...4 bar
Set point definition: Set Point not defined
Process connection: 2x1/4 -NPT-F
Electrical connection: 1/2 -14 NPT-F
Mounting: Enclosure with plate for wall or direct mounting
Diaphragm Material: AISI 304
Brand: WIKA Instruments Italia
Connection: Stainless steel AISI 316L
DA-160UR

Approvals / Certificates

© 2023 - WIKA Instruments s.a.r.l.

IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.