Specifications

Eaton 63NZ02R



Catalog Number: 63NZ02R

Fuse-link, LV, 63 A, AC 400 V, D02, gR, IEC, ultra rapid

General specifications

Product Name
Eaton Bussmann series low voltage D0 fuse

Catalog Number
63NZ02R

EAN
5027590485715

Product Length/Depth
36 mm

Product Height
15 mm

Product Width
15 mm

Product Weight
89.4 g

Compliances
CE Marked
RoHS Compliant

Certifications
IEC 60269
EAC
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

Powering Business Worldwide

Product specifications

Type

fuse

Application

For domestic and general industrial applications

Amperage Rating

63 A

Fuse size

D02

Breaking capacity

50 kA

Rated voltage AC

400 V

Class

Class gR

Fuse type

NZ02R - Ultra rapid

Accessory/spare part type

63GN02 Copper screw cap gauge piece

Utilization category

gR (general purpose semiconductor protection)

Color

Copper

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Connection

Other

Construction

D02

Construction size

D02

Fuse shape

Bottle

Response time

Resources

Brochures

eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf

Catalogs

CA134002EN

Declarations of conformity

UKCA Bottle fuse-links, holders, carriers and accessories

CE Bottle fuse-links, holders, carriers and accessories

Technical service bulletins

Datasheet - 63NZ02R

Ultra rapid

Suitable for

E18 (D02) Fuse base

FRN02C Single-pole fuse base

FN02C Single-pole fuse base

FRN02-D Single-pole fuse base

FRN02-SD Single-pole fuse base

TFRN02C Three-pole fuse base

TFN02C Three-pole fuse base

TFRN02-D Three-pole fuse base

TFRN02-SD Three-pole fuse base

Material

White ceramic body

Voltage rating

400 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia