Handling protection

ULTRANE 527



PATENTED

RESICOMFORT TECHNOLOGY

EN388	EN407	CATEGORY 2
31X1A	X1XXXX	CE

ISO 13997:	DEXTERITY
4.6 N	EN ISO 21420: 5/5

OEKO TEX® STANDARD 100 CQ 979/2 IFTH

Detachable fingers to limit the risk of entanglement by a moving tool - MAPA Patent Pending
Comfort, suppleness and high dexterity without any compromise on breathability and durability

SPECIFIC ADVANTAGES

Protection to limit the risk of entanglement
- Detachable fingers to limit hand risk - Patented MAPA

Comfort
- High suppleness and flexibility dexterity at fingertips proven breathability

Durability
- Extended use guaranteed by our exclusive process RESICOMFORT. Proven breathability, flexibility and durability of the coating.

Skin protection
- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Dermatologically approved

Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability
- Washable 1 time at 40°C

INDUSTRIES
- Automotive/mechanical industry
- Mechanical industry
- Aeronautics industry
- Manufacturing
- Industrial maintenance

APPLICATIONS
- Mechanical maintenance
- Assembly of small parts
- Automotive assembly
- Fitting small screws and fasteners

Edit 30/10/2024

Handling protection

ULTRANE 527

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

3	1	X	1	A	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	15
Exterior finish	Ventilated back
Material	Nitrile foam sandy
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	270000000000 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	8.2E+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 96 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/20/3017
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 30/10/2024