PERFORMANCE MADE SMARTER



Ex-isolated driver

5105B

- 1- or 2-channel version
- 3- / 5-port 3.75 kVAC galvanic isolation
- Driver for Ex / I.S. area
- 20 programmable measurement ranges
- Universal supply by AC or DC

Application
- Safety barrier for current signals transmitted to I/P converters and displays mounted in hazardous area.
- Safety barrier for analog current / voltage signals transmitted to hazardous area.
- 1 : 1 or signal conversion of analog current / voltage signals.

Technical characteristics
- The 20 factory-calibrated measurement ranges in the 5105B can be selected by the internal DIP-switches without the need for a recalibration. Special measurement ranges can be delivered.
- PR5105B is based on microprocessor technology for gain and offset. The analog signal is transmitted at a response time of less than 25 ms.
- Inputs, outputs, and supply are floating and galvanically separated.

Mounting / installation
- Mounted vertically or horizontally on a DIN rail. By way of the 2-channel version up to 84 channels per meter can be mounted.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order:

Type	Input		Output		Channels	
5105B	0...20 mA	: A	Special	: 0	Single	: A
	4...20 mA	: B	0...20 mA	: 1	Double	: B
	0...10 V	: E	4...20 mA	: 2		
	2...10 V	: F	0...1 V	: 4		
	Special	: X	0.2...1 V	: 5		
			0...10 V	: 6		
			2...10 V	: 7		

Environmental Conditions

Operating temperature..... -20°C to +60°C
Calibration temperature..... 20...28°C
Relative humidity..... < 95% RH (non-cond.)
Protection degree..... IP20

Mechanical specifications

Dimensions (HxWxD)..... 109 x 23.5 x 130 mm
Weight approx..... 225 g
DIN rail type..... DIN 46277
Wire size..... 1 x 2.5 mm^2 stranded wire
Screw terminal torque..... 0.5 Nm
Vibration..... IEC 60068-2-6
2...13.2 Hz..... ±1 mm
13.2...100 Hz..... ±0.7 g

Common specifications

Supply

Supply voltage, universal..... 21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Fuse..... 400 mA SB / 250 VAC
Max. required power..... ≤ 2 W (2 channels)
Internal power dissipation..... ≤ 2 W (2 channels)

Isolation voltage

Isolation voltage, test / working..... 3.75 kVAC / 250 VAC
PELV/SELV..... IEC 61140

Response time

Response time (0...90%, 100...10%)..... < 25 ms

Signal / noise ratio..... Min. 60 dB (0...100 kHz)
Accuracy..... Better than 0.1% of sel. range
EMC immunity influence..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst..... < ±1% of span

Input specifications

Common input specifications

Max. offset..... 20% of max. value

Current input

Measurement range..... 0...20 mA
Min. measurement range (span)..... 16 mA
Input resistance..... Nom. 10 Ω + PTC 10 Ω

Voltage input

Measurement range..... 0...10 VDC
Min. measurement range (span)..... 8 VDC
Input resistance..... > 2 MΩ

Output specifications

Current output

Signal range..... 0...20 mA
Min. signal range..... 16 mA
Load (@ current output)..... ≤ 770 Ω
Load stability..... ≤ 0.01% of span / 100 Ω
Current limit..... ≤ 28 mA

Voltage output

Signal range..... 0...1 VDC / 0...10 VDC
Min. signal range..... 0.8 VDC / 8 VDC
Load (@ voltage output)..... ≥ 500 kΩ

of span..... = of the presently selected range

Observed authority requirements

EMC..... 2014/30/EU
LVD..... 2014/35/EU
EAC..... TR-CU 020/2011

Approvals

ATEX 2014/34/EU..... DEMKO 99ATEX126014, II (1) GD [EEx ia] IIC
UL..... UL 913, UL 508
EAC Ex TR-CU 012/2011..... RU C-DK.GB08.V.00410
DNV-GL Marine..... Stand. f. Certific. No. 2.4