Specifications

Eaton 279393



Catalog Number: 279393

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, black, size 2

General specifications

Product Name
Eaton Moeller series NZM operating element

Catalog Number
279393

EAN
4015082793937

Product Length/Depth
100 mm

Product Height
190 mm

Product Width
110 mm

Product Weight
0.672 kg

Compliances
UL/CSA
IEC
RoHS conform

Powering Business Worldwide

Product specifications

Used with

NZM2(-4), PN2(-4), N(S)2(-4)

Type

Accessory Door coupling rotary handle

Special features

Complete including rotary drive and coupling parts For extremely narrow fittings With special short extension shaft Cannot be combined with NZM...-XDZ additional handle External warning plate/designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door

Features

Lockable

Standard: black / gray

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM2

Drawings

eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-005.eps

eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-008.eps

eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps

eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-004.eps

Installation instructions

eaton-circuit-breaker-rotary-handle-nzm1-2-il01219004z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CD-nzm2_xtvd_0

DA-CS-nzm2_xtvd_0

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

Padlock

Extension shaft

Frame

NZM2

Suitable for

Switch disconnector

Power circuit breaker

Cover/door type

Door can be opened in OFF

Door interlock can be modified such that it can be defeated from the outside using a screwdriver

Door interlock not defeated in the locked OFF and ON positions

Door interlock can be modified in the unlocked ON position

Lock number

Single lockable

Locking facility

With door interlock

Lockable on the 0 position on the handle using up to 3 padlocks

Degree of protection / NEMA enclosure type

IP66

4X. 12

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia