Specifications

Eaton 106421



Catalog Number: 106421

Eaton xEnergy Basic LV systems Low voltage switchgear. Metal door, for HxW=2060x600mm, left, white

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	106421
EAN	**Product Length/Depth**
4015081061914	45 mm
Product Height	**Product Width**
2010 mm	615 mm
Product Weight	**Compliances**
10.6 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Floor-standing enclosure
Accessory consideration
Accessory
Service distribution board IVS

Special features

can be used as right door for two-leaf versions
order together with standard door for 600 mm
Closed
Two doors
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock
Protective cover mounted on left

Type

Additional equipment for floor-standing service distribution board IVS

Features

EMC-version

Accessory/spare part type

Doors

Surface finishing

Powder coating
With powder coating

Color

White
Traffic white (RAL 9016)

Degree of protection

IP30
NEMA Other

Unit type

Modular system

Suitable for height

2060 mm

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_Z-DS

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Suitable for width

1200 mm

Cover/door type

Three-point turn-lock

Material

Sheet steel

Steel

Housing material

Sheet steel

Model

Stop door

Mounting method

Surface mounting

Flush mounting

Floor standing distribution board

Functions

Floor-standing enclosure

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia