Specifications

Eaton 272008

Catalog Number: 272008

Eaton Moeller® series LS Position switch, Rounded plunger, Basic device, expandable, 2 N/O, Cage Clamp, Black, Insulated material, -25 - +70 °C



General specifications

Product Name
Eaton Moeller® series LS Position switch

Catalog Number
272008

EAN
4015082720087

Product Length/Depth
33.5 mm

Product Height
76.5 mm

Product Width
31 mm

Product Weight
0.05 kg

Certifications
IEC/EN 60947-5
UL File No.: E29184
UL 508
CSA
UL Category Control No.: NKCR
CSA-C22.2 No. 14
CSA Class No.: 3211-03
CSA File No.: 012528
IEC/EN 60947
CE
UL

Powering Business Worldwide

Product specifications

Type

Position switch

Features

Expandable

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Resources

Catalogs

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Declarations of conformity

DA-DC-00004160.pdf

DA-DC-00004133.pdf

Drawings

eaton-position-switches-plunger-ls-dimensions-002.eps

eaton-position-switches-plunger-ls-dimensions-004.eps

eaton-position-switches-plunger-ls-3d-drawing.eps

eaton-operating-button-symbol-005.eps

eCAD model

ETN.272008.edz

Installation instructions

IL053001ZU

mCAD model

DA-CD-ls

DA-CS-ls

Sales notes

eaton-safety-switches-rs-titan-flyer-fl053001en-en-us.pdf

Wiring diagrams

eaton-position-switches-contact-ls-wiring-diagram-002.eps

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Electric connection type

Cable entry metrical

Enclosure material finishing

Other

Operating frequency

6000 Operations/h

Pollution degree

3

Actuator alignment

Roller cam straight

Climatic proofing

Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

Enclosure material

Insulated material
Plastic

Enclosure type

Cuboid

Rated operational current (Ie) at DC-13, 110 V

0.6 A

Rated operational current (Ie) at DC-13, 125 V

0.8 A

Rated operational current (Ie) at DC-13, 220 V, 230 V

0.3 A

Rated operational current (Ie) at DC-13, 24 V

3 A

Rated operational current for specified heat dissipation (In)

6 A

Sensor height

61 mm

Sensor length

33.5 mm

Static heat dissipation, non-current-dependent Pvs

0 W

Width sensor

31 mm

Product category

Rounded plunger

Action

2020122120328-Mechanical Limit Switches.xlsm-Data

Rated impulse withstand voltage (Uimp)

4000 V AC

Enclosure color

Black (Cover)

Actuating force at beginning/end of stroke

1.0 N/8.0 N

Explosion safety category for dust

None

Explosion safety category for gas

None

Actuator type

Plunger

Actuating torque of rotary drives

0.2 Nm

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Diameter sensor

0 mm

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0.17 W

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

2

Number of safety auxiliary contacts

0

Rated insulation voltage (Ui)

400 V

Rated operational current (Ie) at AC-15, 125 V

6 A

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (Ie) at AC-15, 24 V

6 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V

4 A

Mounting position

As required

Rated conditional short-circuit current (Iq)

1 kA

Overvoltage category

III

Control circuit reliability

1 failure per 10,000,000 switching operations (Statistically

determined, at 24 V DC/5 mA)

1 failure per 5,000,000 switching operations (statistically

determined, at 5 V DC/1 mA)

Connection type

Cage Clamp

Temperature resistance

100 °C, Contact temperature of roller head

Degree of protection

IP66/IP67

NEMA Other

Interface type

None

Switch function type

Slow-action switch

Lifespan

8,000,000 mechanical Operations

Repetition accuracy

0.15 mm (Contacts/switching capacity)

Shock resistance

25 g, Standard-action contact, Mechanical, Half-sinusoidal shock

20 ms

Supply frequency

Max. 400 Hz, Contacts

Operating speed

Max. 1/0.5 m/s (with DIN cam, mechanical actuation)

For angle of actuation $\alpha = 0°/30°$

Short-circuit protection rating

Max. 6 A gG/gL, Fuse, Contacts

Terminal capacity (flexible with ferrule)

1 x (0.5 - 1.5) mm^2

Terminal capacity (solid)

1 x (0.5 - 2.5) mm^2



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia