Specifications

Eaton 262688

Catalog Number: 262688

Eaton Moeller® series ETR2 Timing relay, 0.05s-100h, 24-240VAC 50/60Hz, 24-48VDC, 1W, flashing



General specifications

Product Name
Eaton Moeller® series ETR2 Timing relay

Catalog Number
262688

EAN
4015082626884

Product Length/Depth
63 mm

Product Height
70 mm

Product Width
17.5 mm

Product Weight
0.051 kg

Certifications
Certified by UL for use in Canada
UL 508
CSA File No.: UL report valid
UL
CSA-22.2 No. 14
CSA Class No.: 3211-03
IEC/EN 61812-1
UL File No.: E29184
CE
IEC/EN 60947-5-1
UL Category Control No.: NKCR, NKCR7

Powering Business Worldwide

Features & Functions

Electric connection type

Screw connection

Functions

Flashing, starting with pause, fixed time

Flashing, starting with pulse, fixed time

Fixed timing function

Flashing, pulse initiating

Remote operation possible

General

Degree of protection

IP20

Number of contacts (change-over contacts)

1

Product category

ETR2 timing relays

Suitable for

DIN rail (top hat rail) mounting

Time range - min

0.05 s

Time range - max

360000 s

Type

Timer relay

Voltage type

AC/DC

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Electrical rating

Mains voltage tolerance

24 - 240 V AC (at 50/60 Hz)

24 - 48 V DC

Nominal current

3 A

Rated operational current (Ie)

3 A at 230 V (NC)

3 A at 230 V (NO)

4 A at AC-15, 220 V 230 V 240 V

Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min

24 V

Rated control supply voltage (Us) at AC, 50 Hz - max

240 V

Rated control supply voltage (Us) at AC, 60 Hz - min

24 V

Design verification

Heat dissipation capacity Pdiss

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Rated control supply voltage (Us) at AC, 60 Hz - max

240 V

Rated control supply voltage (Us) at DC - min

24 V

Rated control supply voltage (Us) at DC - max

240 V

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise

calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Brochures

EMR6 - EMT6 - ETR4 brochure

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Characteristic curve

eaton-timers-diagram-timing-relay-characteristic-curve-006.eps

Declarations of conformity

DA-DC-00004675.pdf

DA-DC-00004673.pdf

Drawings

eaton-timers-timing-relay-etr2-dimensions.eps

eaton-timers-timing-relay-etr2-3d-drawing.eps

eCAD model

ETN.262688.edz

Installation instructions

eaton-solid-state-timing-relay-etr2-instruction-leaflet-il04910005z.pdf

mCAD model

etr2_11_d.stp

etr2_42

etr2_11_d

Wiring diagrams

eaton-timers-relay-etr2-timing-relay-wiring-diagram.eps

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.