
The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number JLM508748 - JLM508710, Tapered Roller Bearings - TS (Tapered Single) Metric

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





Specifications | Dimensions | Abutment and Fillet Dimensions | Basic Load Ratings | Factors

Specifications

Series	LM508700
Cone Part Number	JLM508748
Cup Part Number	JLM508710
Design Units	Metric
Bearing Weight	0.600 Kg 1.30 lb
Cage Type	Stamped Steel

Dimensions

d - Bore	60.000 mm 2.3622 in
D - Cup Outer Diameter	95.000 mm 3.7402 in

B - Cone Width	24.000 mm 0.9449 in
C - Cup Width	19.000 mm 0.7480 in
T - Bearing Width	24.000 mm 0.9449 in

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius[1]	5.080 mm 0.200 in
r - Cup Backface "To Clear" Radius[2]	2.54 mm 0.100 in
da - Cone Frontface Backing Diameter	66.04 mm 2.60 in
db - Cone Backface Backing Diameter	74.93 mm 2.95 in
Da - Cup Frontface Backing Diameter	91.90 mm 3.62 in
Db - Cup Backface Backing Diameter	85.09 mm 3.35 in
Ab - Cage-Cone Frontface Clearance	2 mm 0.08 in
Aa - Cage-Cone Backface Clearance	1 mm 0.04 in
a - Effective Center Location[3]	-2.80 mm -0.11 in


Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)[4]	25300 N 5690 lbf
C1 - Dynamic Radial Rating (1 million revolutions)[5]	97600 N 21900 lbf
C0 - Static Radial Rating	135000 N 30400 lbf
C_{a90} - Dynamic Thrust Rating (90 million revolutions)[6]	17400 N 3910 lbf

Factors

K - Factor[7]	1.45
e - ISO Factor[8]	0.4
Y - ISO Factor[9]	1.49
G1 - Heat Generation Factor (Roller-Raceway)	54.2
G2 - Heat Generation Factor (Rib-Roller End)	25.3
Cg - Geometry Factor	0.0979

[1] These maximum fillet radii will be cleared by the bearing corners.
[2] These maximum fillet radii will be cleared by the bearing corners.
[3] Negative value indicates effective center inside cone backface.
[4] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.
[5] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.
[6] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.
[7] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[8] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[9] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



METRIC UNITS

ISO Factor - e	0.4	
ISO Factor - Y	1.49	
Bearing Weight	0.6	kg
Number of Rollers Per Row	23	
Effective Center Location	-2.8	mm

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

JLM508748 - JLM508710
TS BEARING ASSEMBLY

K Factor	1.45	
Dynamic Radial Rating - C90	25300	N
Dynamic Thrust Rating - Ca90	17400	N
Static Radial Rating - C0	135000	N
Dynamic Radial Rating - C1	97600	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY