Specifications

Eaton LP-CC-20

Catalog Number: LP-CC-20

Eaton Bussmann Series Class CC fuse, LP-CC, time-delay, dual-element current limiting fuse, 20 A, rejection Style fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc



General specifications

Product Name	**Catalog Number**
Eaton Bussmann series LP-CC fuse	LP-CC-20
UPC	**Product Length/Depth**
051712180276	1.5 in
Product Height	**Product Width**
0.41 in	0.41 in
Product Weight	**Warranty**
0.15 lb	Not Applicable
Compliances	**Certifications**
CE Marked RoHS Compliant	UL Listed CSA Certified

Powering Business Worldwide

Product specifications

Type

Current-limiting time-delay fuse

Special features

Rejection style

Application

Specialized circuits and industrial control

Amperage Rating

20 A

Number of elements

Dual

Class

Class CC

Interrupt rating

200 kAIC at 600 Vac

20 kAIC at 300 Vdc

Fuse indicator

Non-indicating

Connection

Ferrule end x ferrule end

Response time

12 sec at 200%

Material

Melamine tube

Packaging type

Standard

Quantity

10

Voltage rating

600 Vac, 300 Vdc

Resources

Catalogs

Bussmann Full Line Catalog

Low Voltage Branch Circuit Fuse Chapter

Multimedia

Bussmann series Fuseology

Specifications and datasheets

LP-CC Spec Sheet



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia