# 6993 - POLYMER RUN TEE MALE BSPP FDA NICKEL PLD EPDM SEAL




| | |
|---|---|
| **maximum working pressure** | 16 bar<br>2 MPa<br>232 psi |
| **working temperature** | -10 to 95 °C<br>14 to 203 °F<br>263 to 368 °K |
| **vacuum capability** | 755 mm Hg |
| **body** | BIO-BASED POLYMER |
| **sub-base** | FDA CHEMICAL NICKEL PLATED BRASS |
| **'O'-rings** | EPDM |
| **gripping ring** | STAINLESS STEEL |

• Convert to inch • Convert to oz • Reset Filters

| Part Nb | ØD (MM) | C | E (mm) | F (mm) | ØG (mm) | H (mm) | H1 (mm) | L (mm) | (kg) |
|---|---|---|---|---|---|---|---|---|---|
| | All | All | All | All | All | All | All | All | All |
| 6993 04 10 | 4 | G1/8 | 5 | 13 | 8.5 | 30 | 18 | 14.5 | .009 |
| 6993 04 13 | 4 | G1/4 | 5.5 | 16 | 8.5 | 30 | 18 | 14.5 | .014 |
| 6993 04 19 | 4 | M5x0,8 | 3.5 | 8 | 8.5 | 32 | 19 | 14.5 | .006 |
| 6993 06 13 | 6 | G1/4 | 5.5 | 16 | 10.5 | 38 | 22 | 17.5 | .016 |
| 6993 06 19 | 6 | M5x0,8 | 3.5 | 10 | 10.5 | 39 | 23 | 17.5 | .009 |
| 6993 08 10 | 8 | G1/8 | 4.5 | 13 | 13.5 | 54 | 31 | 23 | .019 |
| 6993 08 17 | 8 | G3/8 | 5.5 | 20 | 13.5 | 52 | 29 | 23 | .03 |
| 6993 10 17 | 10 | G3/8 | 5.5 | 20 | 16 | 61 | 35 | 26.5 | .055 |
| 6993 10 21 | 10 | G1/2 | 7.5 | 24 | 16 | 61 | 35 | 26.5 | .051 |
| 6993 12 17 | 12 | G3/8 | 5.5 | 20 | 19 | 67 | 36 | 31 | .042 |