Rittal – The System.

Faster – better – everywhere.



DK 7246.400

Adaptor, 3 U

State: 30/1/2023 (Source: rittal.com/in-en)

DK 7246.400 - Adaptor, 3 U Depth offset 100 mm

Used to recess 482.6 mm (19˝) mounting of equipment inside enclosures with 482.6 mm (19˝) installation in the foremost position, such as server or electronic enclosures.



Features

Model No.	DK 7246.400
Product description	This adaptor is used to recess 482.6 mm (19") mounting of equipment inside enclosures with 482.6 mm (19") installation in the foremost position, such as server or electronic enclosures. In this way, sufficient space can be gained in front of the mounting equipment to integrate patch panels or switches, whilst at the same time exploiting the maximum enclosure depth.
Material	Sheet steel
Surface finish	Zinc-plated
Supply includes	Assembly parts
Units	3 U
Installation dimensions	Installation depth for components: 482.6 mm Installation width for components: 19"
Packs of	2 pc(s).
Weight/pack	0.36 kg
Copper weight (kg per piece)	0
Customs tariff number	73269098
EAN	4028177389830
ETIM 7.0	EC002625

Features

ECLASS 8.0	27189234

Approvals

Approvals	GOST

Tender text

482.6 mm (19") adaptor, 3 U, 100 mm depth offset
Material: Sheet steel, zinc-plated, passivated