Date: 12/04/2023

PSD-4; 0...1 bar gauge ; one switching output (PNP/NPN) + 4...20 mA

PSD-4; 0...1 bar gauge ; one switching output (PNP/NPN) + 4...20 mA

Item number: 48762832

Quantity: 1 pcs.

Order code: PSD-4-AZ-BG310-GDSZ-WW-ZZ W1011PS4Z-SZAB-P-GSFI

Overview:
PSD-4; 0...1 bar gauge ; one switching output (PNP/NPN) + 4...20 mA
Electronic pressure switch with display
Output signal: one switching output (PNP/NPN) + 4...20 mA
IO-Link: without
Power supply: 15...35 V DC
Measuring range: 0...1 bar gauge
Process connection: G 1/2 B
Sealing: stainless steel
Media temperature: -20 … 85 °C (-4 ... +185 °F)
El. connection: Circular connector M12x1 (4-pin)
pin assignment el. connection: U+=1, U-=3, S+=2, SP1=4
Accuracy: ± 0.5% of span
Approvals: cULus
with test protocol
Specifications according to data sheet: PE 81.86

Details:
PSD-4; 0...1 bar gauge ; one switching output (PNP/NPN) + 4...20 mA
Electronic pressure switch with display
Output signal: one switching output (PNP/NPN) + 4...20 mA
IO-Link: without
Power supply: 15...35 V DC
Measuring range: 0...1 bar gauge
Process connection: G 1/2 B
Sealing: stainless steel
Media temperature: -20 … 85 °C (-4 ... +185 °F)
El. connection: Circular connector M12x1 (4-pin)
pin assignment el. connection: U+=1, U-=3, S+=2, SP1=4
Accuracy: ± 0.5% of span
Approvals: cULus
with test protocol
Specifications according to data sheet: PE 81.86

© 2023 - WIKA Instruments s.a.r.l.