Date: 12/04/2023

TAGUS-0 ... +400 °C - 1/2 NPT male - 1/2 -14 NPT-F

Gas-actuated temperature switch, flameproof switch enclosure Ex d

Item number: 48799524

Quantity: 1 pcs.

Order code: TAGUS-ZZ-CBEB-EAMZZZA-1ZZ ZC
F6-C4-C5- - - -

Overview:
TAGUS-0 ... +400 °C - 1/2 NPT male - 1/2 -14 NPT-F
Gas-actuated temperature switch, flameproof switch enclosure Ex d TAG
Contact version: 1x SPDT silver contact, hermetically sealed, argon gas filling
setting range: 0 ... +400 °C, working range -40 ... +400°C, proof temperature +500°C
Process connection: 1/2 NPT male
Electrical connection: 1/2 -14 NPT-F
Mounting: Enclosure with plate for wall or direct mounting
Sensor Dimensions: active length X = 85 mm, insertion length Ymin = 145 mm, Ymax = 300 mm
Brand: WIKA Instruments Italia
Specifications according to data sheet: TV 31.61
Repeatability of set point: ≤ 0,5% of span

Set point definition: Set Point not defined
Approvals / Certificates
SIL2 for functional safety
IECEx-ATEX Ex d

Details:
Gas-actuated temperature switch, flameproof switch enclosure Ex d
Model TAG
Specifications according to data sheet: TV 31.61
Repeatability of set point: ≤ 0,5% of span
0 ... +400 °C, working range -40 ... +400°C, proof temperature +500°C
Set Point not defined
1x SPDT silver contact, hermetically sealed, argon gas filling
Process connection: 1/2 NPT male
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
active length X = 85 mm, insertion length Ymin = 145 mm, Ymax = 300 mm
Brand: WIKA Instruments Italia
Unit: °C
TAGUS
Approvals / Certificates
SIL2 for functional safety
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.