HOSE COILS

DIFLEX PVC HOSE - COIL



FOOD INDUSTRY

ID/OD (mm)	Coil (m)	Bend radius (mm)	Max operating pressure (bar)	Colour	Part Numbers
6 x 12	50	36	15	Blue	**DIFLEX 6**
8 x 14	50	54	15	Blue	**DIFLEX 8**
8 x 14	50	54	15	Red	**DIFLEX 8RG**
8 x 14	25	54	15	Blue	**DIFLEX 8C25**
9 x 15	50	66	15	Blue	**DIFLEX 9**
10 x 16	50	74	15	Blue	**DIFLEX 10**
10 x 16	50	74	15	Red	**DIFLEX 10RG**
10 x 16	25	74	15	Blue	**DIFLEX 10C25**
12 x 19	50	90	15	Blue	**DIFLEX 12**
12 x 19	50	90	15	Red	**DIFLEX 12RG**
13 x 20	50	101	15	Blue	**DIFLEX 13**
13 x 20	50	101	15	Red	**DIFLEX 13RG**
16 x 22	25	145	15	Blue	**DIFLEX 16**
19 x 26	25	174	15	Blue	**DIFLEX 19**
25 x 33	25	260	15	Blue	**DIFLEX 25**
32 x 42	25	320	12	Clear	**DIFLEX 32**
38 x 48	25	420	11	Clear	**DIFLEX 38**
50 x 64	25	600	8	Clear	**DIFLEX 50**

Temperature: -15°C to +60°C

AIRCA RUBBER HOSE - COIL



ID/OD (mm)	Coil (m)	Bend radius (mm)	Max operating pressure (bar)	Colour	Part Numbers
6 x 13	40	18	20	Blue - Black	**AIRCA 6**
8 x 15	40	25	20	Blue - Black	**AIRCA 8**
8 x 15	20	25	20	Blue - Black	**AIRCA 8C20**
10 x 18	40	35	20	Blue - Black	**AIRCA 10**
13 x 22	40	60	20	Blue - Black	**AIRCA 13**
16 x 25	40	70	15	Blue - Black	**AIRCA 16**
19 x 28	40	80	15	Blue - Black	**AIRCA 19**
25 x 34	40	100	15	Blue - Black	**AIRCA 25**

Rubber hose with alternating blue and black stripes
Outer sheath made from smooth black EPDM
Inner lining made from smooth black SBR, reinforced with a synthetic fabric braid
Lubricated air supply for pneumatic tools
Temperature: -40°C to +70°C