Specifications

Eaton 260150



Catalog Number: 260150

Eaton Moeller series NZM - Molded Case Circuit Breaker. Control circuit terminal, screw connection, NZM1

General specifications

Product Name
Eaton Moeller series NZM connection type

Catalog Number
260150

EAN
4015082601508

Product Length/Depth
21 mm

Product Height
12.5 mm

Product Width
25 mm

Product Weight
0.021 kg

Compliances
IEC
UL/CSA
RoHS conform

Certifications
CSA certified
UL (Category Control Number DIHS)
UL listed
CSA-C22.2 No. 5-09
UL (File No. E140305)
CSA (File No. 22086)
CE marking
UL489
CSA (Class No. 1437-01)
IEC60947

Powering Business Worldwide

Product specifications

Used with

NZM1(-4), PN1(-4), N(S)1(-4)

Type

Accessory Control circuit terminal Terminal

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM1

Drawings

eaton-circuit-breaker-terminals-nzm-screw-dimensions.eps

eaton-circuit-breaker-terminals-nzm-screw-3d-drawing-002.eps

eCAD model

DA-CE-ETN.NZM1-XSTS

Installation instructions

eaton-side-wall-actuator-nzm1-xs-xzb-il01203006z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

nzm1_xsts.dwg

nzm1_xsts.stp

Technical data sheets

eaton-nzm-technical-information-sheet

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM1

Suitable for

Screw connection

Core cross section

2.5 mm²

Number of poles

Single-pole

Terminal capacity (stranded cable)

0.75 mm² - 1.5 mm² (2x)
18 - 16 AWG/kcmil (2x)
0.75 mm² - 2.5 mm² (1x)
18 - 14 AWG/kcmil (1x)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia