EVO8®

EN14052 HIGH IMPACT HELMET - WHEEL RATCHET - VENTILATED

PRODUCT CODE: AHU150-00_-_00

THE WORLDS STRONGEST INDUSTRIAL SAFETY HELMET

TECHNICAL SPECIFICATION

HEAD PROTECTION

INSTRUCTIONS FOR USE


- Fit helmet on head and fasten strap to ensure fit
- For adequate protection this helmet must be worn with peak facing forward
- Ensure the helmet is adjusted to the size of the user's head

SHELL:
Recyclable UV Stabilised HDPE with Expanded Polystyrene (EPS) liner



COMFORT:
Extremely comfortable terylene webbing moulds to the individual wearer's head. Lightweight EPS liner reduces weight while still offering maximum protection

WEBBING HARNESS:
LDPE Strap & Webbing Clips with Nylon Webbing Straps Microfibre comfort padding



WHEEL RATCHET:
Intuitive thumb and fore finger press points for easy adjustment of the wheel ratchet, offers diverse size ranges for true 'One Size Fits All'



DESIGN RIGHTS RESERVED • JSP • DESIGN RIGHTS RESERVED

evo8® Mk8 evolution

CONFORMITY

- Conforms to EN 14052, Higher Performance Industrial Safety Helmet
- ANSI Z89.1-2009, American National Standard for Industrial Head Protection, as a Type II, Class E Helmet
- Also conforms to ГОСТ Р 50460-92
- High comfort fit
- Wide size range (adjustment 53-64cm)
- Available in a choice of colours
- Company personalisation available by printing
- Accessories available

CLEANING & MAINTENANCE

- The unit may be cleaned with soap and warm water and dried with a soft cloth
- The helmet should not be cleaned with chemical or abrasive cleaners
- The helmet should be stored out of direct sunlight
- The helmet should be stored away from chemicals and extremes of temperature

EVO8®

EN14052 HIGH IMPACT HELMET - WHEEL RATCHET - VENTILATED

PRODUCT CODE: AHU150-00_-_00

THE WORLDS STRONGEST INDUSTRIAL SAFETY HELMET

TECHNICAL SPECIFICATION

HEAD PROTECTION



DIMENSIONS OF OUTER PACKAGING

Quantity: 8

Weight: 4.85kg (Approx.)



HEIGHT: 466mm

LENGTH: 590mm

WIDTH: 255mm

DIMENSIONS OF HELMET

Size: 530mm x 640mm

Weight: 550g (Approx.)

LOGOEXPRESS™
ADD YOUR LOGO TO OUR PRODUCTS

HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet



01 White 02 Yellow 05 Blue

HELMET FEATURES

EN STANDARD	EN14052 EN397 EN50365	Yes Yes Yes
PERFORMANCE	Impact Resistance Side Impact Electrical Insulation	100 Joules 50 Joules EN50365 1000V
TEMPERATURE RESISTANCE	+50°C Low Temperature	Yes Yes: EN397 -40°C ГОСТ Р 50460-92 -40°C
SHELL MATERIAL	HDPE Recyclable UV Stabilised	Yes Yes Yes
HARNESS MATERIAL	LDPE Textile	Yes Yes
OPTIONS	Universal Accessories Ventilated 4pts Chin strap	Yes Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Wheel Ratchet 6 pts	Yes Yes Yes
LOGO OPTIONS	Front Side MOQ Logo	Yes Yes 40

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer