Specifications

Eaton 167435

Catalog Number: 167435

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, high, maintained, orange, Blank, Bezel: titanium

General specifications

Product Name
Eaton Moeller® series M22 Illuminated pushbutton actuator

Catalog Number
167435

EAN
4015081639359

Product Length/Depth
30 mm

Product Height
30 mm

Product Width
30 mm

Product Weight
0.013 kg

Certifications
CSA
CSA Class No.: 3211-03
CSA-C22.2 No. 14-05
IEC/EN 60947
UL File No.: E29184
UL
IEC/EN 60947-5
CSA File No.: 012528
CE
UL Category Control No.: NKCR
CSA-C22.2 No. 94-91
UL 508
VDE 0660
DNV
GL
LR

Features & Functions

Bezel color
Titanium

Bezel material
Plastic

Design
High
Classical

Fitted with:
Front ring

Functions
Stay-put/spring-return function can be changed on device

Inscription
Blank

General

Degree of protection
IP66
IP67
NEMA 3R
NEMA 12
NEMA 4X
NEMA 13
IP69K

Degree of protection (front side)
NEMA 4X
IP67/IP69K

Lifespan, mechanical
1,000,000 Operations (AC operated)

Opening diameter
22.5 mm

Operating frequency
1800 Operations/h

Product category
RMQ-Titan

Size
Front diameter: 29.7 mm

Suitable for
Illumination

Type
Illuminated pushbutton actuator

Ambient conditions, mechanical

Shock resistance
Mechanical, According to IEC/EN 60068-2-27
30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Climatic environmental conditions

Ambient operating temperature - min
-25 °C

Ambient operating temperature - max
70 °C

Climatic proofing
Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78

Communication

Actuator

Connection to SmartWire-DT

With SWD-RMQ connections

Yes

Actuating force

5 N

Actuator color

Orange

Actuator function

Switching function latching

Maintained

Contacts

Force for positive opening - min

0 N

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Catalogs

eaton-rmq-titan-brochure-br047004en-en-us.pdf

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Flip catalog - Product Range Catalog - Command and indication

Declarations of conformity

DA-DC-00004135.pdf

DA-DC-00004157.pdf

Drawings

eaton-operating-pushbutton-m22-dimensions.eps

eaton-operating-pushbutton-m22-dimensions-005.eps

eaton-general-m22-symbol.eps

eaton-general-approval-m22-symbol.eps

eaton-operating-samrtwire-m22-3d-drawing-002.eps

eaton-operating-button-m22-symbol.eps

eaton-general-m22-standards.eps

eCAD model

ETN.167435.edz

Installation instructions

IL04716002Z

Installation videos

RMQ Flat Design

mCAD model

DA-CS-drucktaste_hoch

DA-CD-drucktaste_hoch

Multimedia

RMQ small E-Stop emergency-stop button

MCI MultiColor Light Indicator RMQ compact solution

easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

MCI Multicolor Light Indicator M22 with SmartWire-DT

Sales notes

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf

eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia