Completely pre-assembled Signal Towers / eSIGN

# eSIGN 15 Segments with Siren




**Part No.: 657.600.55**

RoHS 2 2011/65/EU

| MECHANICAL DATA | |
|---|---|
| Height | 372 mm |
| Diameter | 72 mm |
| Materials | PC |
| Dome colour | Clear |
| Housing colour | Black |
| Protection category | IP66<br>IP69K |
| Connection | M12 plug 8-pole |
| Type of fixing | Base mounting<br>Tube mounting |
| Working temperature minimum | -30°C |
| Working temperature maximum | +60°C |

| ELECTRICAL DATA | |
|---|---|
| Operating voltage | 24V |
| Operating voltage type | DC |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 620 mA |
| Rated inrush current | 800 mA |
| Protection class | Protection class 3 |
| Pollution degree | 3 |
| Overvoltage category | I |
| Request to external PSU | SELV/PELV |
| connectivity | Digital entrance<br>USB |

| OPTICAL DATA | |
|---|---|
| Light source | LED |
| Light colour | MC >1.000.000 colours |
| Optical signal image | Blink<br>Double flash<br>Flash<br>Permanent<br>Revolving<br>Triple flash |
| Service life optical | 50,000 h maximum |

| ACUSTICAL DATA | |
|---|---|
| Volume (max) at 1m distance | 105 dB |
| Acoustic signal image | Multi-tone |

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Completely pre-assembled Signal Towers / eSIGN

# eSIGN 15 Segments with Siren

| | |
|---|---|
| Number of tones | 10 tone |
| Acoustic service life | 5,000 h minimum |

| **APPROVAL DATA** | |
|---|---|
| Conforms with CE | No |
| WEEE | Yes |
| Conforms with RED directive | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC-Ex | No |
| Conforms with CCC | No |
| Conforms with UL | No |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | No |
| Conforms with UKCA (Importer) | No |
| Conforms with CMIM | No |
| Conforms with AS-I | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.