EMPTY ENCLOSURE

# GEOS-L 4050-22-o



## GEOS-L 4050-22-o

**Empty enclosure**
400 x 500 x 226 mm
Article number: 70074501

Empty enclosure - Industrial Quality -, suitable for installation in harsh environments and unprotected exterior areas, Base: glass fibre reinforced polycarbonate, Grey, similar to RAL 7035, Cover: Polycarbonate

with grey cover

## Technical data

### Measures

| | |
|---|---|
| Width: | 400 mm |
| Length: | 500 mm |
| Height: | 226 mm |
| Inner height: | 204 mm |
| Inner width: | 371 mm |
| Inner length: | 471 mm |

### Material:

| | |
|---|---|
| material: | Polycarbonate |
| Box: | polycarbonate, glass fiber-reinforced |
| Cover: | Polycarbonate |
| Sealing: | Elastomer |
| Cover screw: | polyamide, fiberglass-reinforced |

## Accessory

- SRS 60-90 - Screw clamp set
- GEOS-L EP-4050 - Mounting plate
- GEOS MH-22 - Mounting holder
- GEOS-L TW 40-22 - Partition wall
- GEOS-L TW 50-22 - Partition wall
- GEOS NS35-350 - Standard rail
- GEOS NS35-450 - Standard rail
- GEOS ABL-10 - External fixing lug
- GEOS ABL-40 - External fixing lug
- GEOS MPI-4050 - Mounting plate
- GEOS MPS-4050 - Mounting plate
- BEL Air M40 - Ventilation element set
- LFR M40 - Hole cutter
- GEOS MSS-40 - Mast clamp set
- GEOS MSS-50 - Mast clamp set
- SRS 90-150 - Screw clamp set


**Günther Spelsberg GmbH + Co. KG** · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299

EMPTY ENCLOSURE

# GEOS-L 4050-22-o

## Other attributes

| | |
|---|---|
| Combustion behaviour acc. to UL 94: | V-2 acc. UL 94 |
| Combustion behaviour to UL 50 / UL 746C: | 5VA nach UL 50 / UL 746C |
| Combustion behaviour acc. to VDE: | 960°C acc. VDE 0471/ EN 60695 |
| Ingress protection: | IP66/IP67 acc. EN 60529 / DIN VDE 0470-1 |
| Impact resistance: | IK09 acc. DIN EN 50102 / VDE 470 segment 100 |
| Color: | Grey |
| Rated insulation voltage AC: | 1000 V |
| Rated insulation voltage DC: | 1500 V |

## Environmental attributes

| | |
|---|---|
| Ambient temperature (min.): | -35 °C |
| Ambient temperature (max.): | 80 °C |
| Ambient temperature (24 h): | 60 °C |
| Max. rel. humidity at 25° C (short term): | 95% |
| Max. rel. humidity at 40° C: | 50% |


**Günther Spelsberg GmbH + Co. KG** · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299