Date: 12/04/2023

P-30 ; 0...6 bar abs; 4...20 mA, 2-W

Pressure sensor for precision measurements Type P-30

Item number:	47454540
Quantity:	1 pcs.
Order code:	P-30-R-BA360-GBZZ-A-A4Z-ZZ W1011DA1-Z2L-2ANZMZZ-PGSDA
Overview:	P-30 ; 0...6 bar abs; 4...20 mA, 2-W @ 9...30 V DC; Accuracy: 0.05% of span G1/4B 4-pin L-plug DIN EN 175301-803, IP65 UB=1, 0V=2 shield: not connected Specifications according to data sheet: PE 81.54
Details:	Pressure sensor for precision measurements Type P-30 Specifications according to data sheet: PE 81.54 Accuracy: 0.05% of span Measuring range: 0...6 bar abs Process connection: G 1/4 B Version for specific media: none Output signal: 4 ... 20 mA, 2-wire Electrical connection: 4-pin L-plug DIN EN 175301-803, IP65 www.wika.com Model name customer-specific: P-30 Pressure port: Standard Permissible medium temperature: -20...+105°C Pin assignment: UB=1, 0V=2 shield: not connected Power supply: 9...30 V DC with test protocol *Made in Germany* on label WIKA standard - specification according to data sheet

© 2023 - WIKA Instruments s.a.r.l.