Specifications

Eaton 102438



Catalog Number: 102438

Eaton xEnergy Basic LV systems Low voltage switchgear. Glass door, for HxW=2060x400mm, Clip-down-handle

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	102438
EAN	**Product Length/Depth**
4015081023264	45 mm
Product Height	**Product Width**
2010 mm	415 mm
Product Weight	**Compliances**
5.2 kg	RoHS conform

Powering Business Worldwide

Product specifications

Special features

Transparent doors
Single wing door
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock
Transparent panels from 4 mm safety glass (EN 12150-1, DIN 1249)

Type

Additional equipment for floor-standing service distribution board
IVS

Features

Version as glazed door
EMC-version

Accessory/spare part type

Doors

Surface finishing

With powder coating
Powder coating

Color

Gray
Light gray (RAL 7035)

Degree of protection

IP30
NEMA Other

Unit type

Modular system

Suitable for height

2060 mm

Suitable for width

400 mm

Cover/door color

Transparent

Cover/door type

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Rotary lever

Material

Sheet steel/glass

Steel

Housing material

Sheet steel/glass

Model

Stop door

Mounting method

Floor standing distribution board

Functions

Floor-standing enclosure

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia