DATASHEET - SL4-PIB-IMH

Base module;internal fixing holes

Part no.	**SL4-PIB-IMH**
	171300
EL Number (Norway)	**4137536**

Product name	Eaton Moeller® series SL4 Base module
Part no.	SL4-PIB-IMH
EAN	4015081679188
Product Length/Depth	43 millimetre
Product height	71 millimetre
Product width	43 millimetre
Product weight	0.055 kilogram
Certifications	UL Category Control No.: NKCR CE IEC/EN 60947-5-1 UL report applies to both US and Canada UL File No.: E29184 UL IEC/EN 60529 CSA Class No.: NKCR7 CSA-C22.2 No. 14-10 UL 508 Certified by UL for use in Canada CSA-C22.2 No. 94-91
Product Tradename	SL4
Product Type	Base module
Product Sub Type	None
Color	Other
Fitted with:	Cover Internal (on the inside) fixing holes
Number of modules	Max. 10 (with base for mounting on both sides) Max. 5 Max. 5 (with standard base)
Connection to SmartWire-DT	No
Degree of protection	IP66 NEMA 1
Mounting Method	Floor Horizontal Bracket
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Type	Base module
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacity (AWG)	24 - 16
Terminal capacity (flexible with ferrule and plastic collar)	0.25 - 0.75 mm^2
Terminal capacity (solid/flexible)	0.2 - 1.5 mm^2
Terminal capacity (solid/flexible with ferrule)	0.25 - 1.5 mm^2

Rated insulation voltage (Ui)			250 V
Rated operational voltage			110/120 V AC ± 10 % 24 V AC/DC ± 10 % 230/240 V AC ± 10 %

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module (ecl@ss10.0.1-27-37-12-32 [AKF050014])

Connection type auxiliary circuit			Spring clamp connection
Suitable for tube mounting			No
Suitable for bracket mounting			Yes
Suitable for floor mounting			Yes
Colour			Other
Suitable for AS interface			No

© 04/2023 by Eaton Industries GmbH