SUREFIT™ POLYCARBONATE VISOR UNBOUND

AVAILABLE IN 17.5cm OR 20cm

OFFERS PROTECTION AGAINST MEDIUM ENERGY HIGH-SPEED PARTICLES, LIQUID DROPLETS & MOLTEN METAL

TECHNICAL SPECIFICATION

HEAD PROTECTION

ACCESSORIES

INSTRUCTIONS FOR USE

- In use ensure that the faceshield fits comfortably and securely on the head
- Ensure that a suitable visor has been fitted with the protective film removed from it
- Ensure the visor is in place before entering the hazard area

CONFORMITY

- Meets the requirements of EN 166
- EU Type Examination Certificate Number 682750, issued by BSI

DIMENSIONS OF VISOR

- Weight: 84g (Approx.)
- Size: 530 - 620mm
- Length: 175mm or 200mm
- Thickness: 1mm

VISOR CARRIER:
Mineral Filled Polypropylene C/W ABS fittings and Steel Spring



DIMENSIONS OF OUTER PACKAGING

- Quantity: 200
- Weight: 20.7kg (Approx.)



HEIGHT:
205mm

WIDTH:
420mm

LENGTH:
445mm

VISOR & CHINGUARD:
Clear Polycarbonate

VISOR PERFORMANCE

- 17.5cm or 20cm Polycarbonate
- Offers protection against medium energy high speed particles at 120 m/s (270mph), liquid droplets and molten metal
- The optical qualities of the visor comply with the requirements of optical class 1 (highest)
- Markings: EN166 1.B.3.9

LIMITATIONS OF USE

- Protection will only be offered if the visor carrier and a visor are fitted correctly to a suitable Industrial Safety Helmet with the helmet attachment kit
- If the visor becomes scratched or damaged they should be replaced, likewise if the visor is subjected to severe impact it should be replaced immediately
- Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer
- The visor, when in contact with the skin may cause allergic reactions to susceptible individuals
- If this occurs leave the hazard area, remove the eyeshield and seek medical advice
- The visor is not suitable for use with all chemicals - if you are unsure contact your supplier or JSP for help and advice

CLEANING & MAINTENANCE

- The visor may be cleaned with soap and warm water and dried with a soft cloth
- Do not clean with chemical or abrasive cleaners
- The visor should be stored out of direct sunlight away from chemicals and extremes of temperature

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com.