PILZ
THE SPIRIT OF SAFETY

PSEN rs2.0-175 570303



Rope pull switch incl. E-STOP pushbutton, plastic housing, 2xNC+2xNO contacts, 175 N max. spring force.

Technical details

General data	
Approval:	CE, UKCA, BG, cCSAus, EAC (Eurasian)
Technical data	
Relay outputs	
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	240 V
Max. current AC15 safety cont.:	3 A
Environmental data	
Ambient temperature:	-25 - 70 °C
Mechanical data	
Housing material lower section:	PA
Housing material upper part:	PA
Material actuator:	Zn die cast
Connection terminal:	Cage clamp terminal
Height dimension:	76.8 mm
Width dimension:	294 mm
Depth dimension:	42.5 mm
Net weight:	680 g
Gross weight:	775 g
Environment	

RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6a, 6b
REACh compliance:	contains min. 1 SVHC-substance
REACh included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
SCIP entry available:	0
Commercial data	
Harmonized System Code:	85365080
UNSPSC 25:	39122205
EAN-Code:	4046548062823
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27270607
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002033
Volume:	0 dm3

Optional accessories



380706 PDP67 cable M12-5sm, 10m



380707 PDP67 cable M12-5sm, 20m

	380705	PDP67 cable M12-5sm, 3m
	570314	PSEN rs rope d3/d4 50m
	380708	PDP67 cable M12-5sm, 30m
	570315	PSEN rs rope d3/d4 100m
	570312	PSEN rs pulley 75
	570313	PSEN rs pulley flex
	570310	PSEN rs spring 175
	773600	PDP67 F 8DI ION
	570311	PSEN rs spring 300



570793 PSEN cable 200m-8x0.25mm²