Terminal block

Abox 250/350 KLS-25²/35²



Abox 250/350 KLS-25²/35²

Terminal block

Productnumber: 84003501
Dimensions: 277 x 66 x 18 mm

Connecting terminal acc. to DIN EN 60998 (VDE 0613), Ui=690V

5-pole - 35 mm²

Created at 04.07.2023. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Rated current:	125 Ampere
Number of poles:	5
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	4
Connection 1: Suitable for Cu conductors:	1
Connection 1: Connectable conductor cross-section, single-wire (min):	10 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	35 mm²

Dimensions

Width:	277 mm
Length:	66 mm
Height:	18 mm

Material characteristics

Industry quality:	no
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	960 °C

mechanical properties

Connection 1: Tightening moment:	4 Nm

Material

Insulating body material:	Thermoplastic

Certificates

Test mark:	VDE (DIN 60998-1/-2-1 (VDE 0613-1/-2-1))