Specifications

Eaton 091469



Catalog Number: 091469

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar terminal, for 1x30x10 Cu bar

General specifications

Product Name
Eaton xEnergy Safety Ci busbar enclosure accessory

Catalog Number
091469

EAN
4015080914693

Product Length/Depth
85 mm

Product Height
40 mm

Product Width
90 mm

Product Weight
0.301 kg

Compliances
RoHS conform

Powering Business Worldwide

Product specifications

Used with

Cu 2 x (40 mm x 10 mm) busbars
Cu 2 x (30 mm x 10 mm) busbars
Ci insulated enclosure
Accessory for busbar enclosures
Prepared enclosures

Special features

In conjunction with K20X5, K20X10, K20X15 busbar terminals

Type

Accessory for busbar enclosures
Ci insulated enclosure
Prepared enclosures

Accessory/spare part type

Busbar terminals

Width clamp

30 mm

Busbar thickness - max

10 mm

Busbar thickness - min

10 mm

Busbar width - max

40 mm

Busbar width - min

30 mm

Conductor cross section - max

231 mm^2

Rated operational current (Ie) - max

1600 A

Functions

Connection for flat cable and cu bar

Rated operation current (Ie)

630 A
100 A

Suitable for

Flat rail
Strip conductor connection

Resources

Brochures

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf

Catalogs

eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf

Drawings

eaton-insulated-boards-busbar-xenergy-safety-ci-busbar-terminal-3d-drawing-003.eps

Rated operational current

1600 A

Terminal capacity (flat strip)

9 mm x 0.8 mm (3x) - 21 mm x 1 mm (6x)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia