Handling protection

ULTRANE 526

Grip assured, skin protected and unbeatable fingertip sensitivity in very oily environments.



GRIP & PROOF TECHNOLOGY

EN388	EN407	
4121A	X1XXXX	ISO 18889
CATEGORY 3	ISO 13997:	DEXTERITY
	4.9 N	EN ISO 21420: 5/5

CE 0334

OEKO TEX® STANDARD 100 CQ 979/2 IFTH

SPECIFIC ADVANTAGES

Comfort
- Unbeatable fingertip sensitivity

Durability
- Excellent abrasion resistance due to the nitrile coating

Productivity
- Grip and Proof coating ensures an excellent grip in very oily environment . It also reduces muscle strain and boosts productivity

Skin protection
- Oilproof, it repels oil penetration and reduce dermatitis
- Free of harmful substances: DMF Free

Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability
- Washable 3 times at 40°, to extend lifespan, reduce costs and waste

Care for the environment
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES
- Automotive/mechanical industry
- Mechanical industry
- Local Authorities (Parks and Public Spaces)
- Glass industry
- Agriculture sector

APPLICATIONS
- Handling glass sheets
- Re-entry tasks
- Assembly of small oily parts
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Public park maintenance
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Machining parts using cutting oil
- Mechanical maintenance

Edit 28/11/2024

Handling protection

ULTRANE 526

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	1	2	1	A	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread



ISO 18889 — PROTECTION FROM PESTICIDES

GR: Re-entry tasks

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Fully-coated
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black
European sizes	7 8 9 10 11

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 96 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953 Ext 01/09/18 update 01-08/09/2023
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 28/11/2024